

Item no.: 389823

## OAIZ - Fibre optic stripping pliers one fibre

## from 132,35 EUR

Item no.: 389823 shipping weight: 0.10 kg Manufacturer: Televes



## Product Description

Stripping and cutting tool for quick, safe and precise removal of both the sheath and the various coatings applied to the fibre (900 and 250µm). With 4 areas:- Cutting area (4): Facilitates the cutting of the fibre or its outer sheath, thus avoiding exchanges between tools, which has a direct impact on working times.- Fibre sheath removal area (3): Allows the removal of fibre sheaths with a diameter of 3 to 1.6 mm, thus providing access to the fibre in question. Fibre sheath removal zone (3): Allows the removal of fibre sheaths with a diameter of 3 to 1.6 mm and thus access to the fibre in question-900µm protection/coating removal zone (2): This zone allows us to remove the 900µm protection/coating and reduce the diameter of the protection to 250µm - 250µm protection/coating removal zone (1): Using this zone, we can remove the protection/coating and reduce the fibre diameter to 125µm (working diameter for fusion)The factory pre-calibrated cutting and stripping blade is designed to avoid scratches or cuts in the fibre to ensure a high quality finish. It has an automatic return system at maximum opening (spring) to make work easier and reduce time. In addition, it has a safety lock to avoid possible injuries during transport and to ensure minimum transport stress. Highlights- Enables the outer and inner coating of the fibre to be stripped- Suitable for use with fibres of different diameters: 250 µm and 900 µm. Ergonomic handle that provides a comfortable grip and high grip thanks to its rubber coating- Indispensable tool for general fibre optic work and especially for preparing the fibre for fusion splicingPhysical data- Net weight:111 g- Gross weight: 111 g- Width: 77 mm- Height: 153 mm- Depth: 10 mm- Main product weight: 124 gPackaging- Bag 1 pc.

## Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

