

Item no.: 389982

OLT1550K - Optical transmitter 2 x SAT wideband in 1550 NM

from **531,07 EUR**

Item no.: 389982
shipping weight: 0.80 kg
Manufacturer: Teledes



Product Description

CWDM optical transmitter specially designed for indoor installation. This device receives a satellite signal from an RF broadband LNB and terrestrial band and distributes it to up to 64 users via an optical fibre output in the 1550nm window with 9dBm optical power. Thanks to its optimised technology and low losses, the number of amplifiers required can be reduced, making it easy to use in shared installations while maintaining signal quality throughout operation. In addition, it is suitable for use in GPON installations and adapts to various solutions. This device is part of the Overlight system, which distributes satellite and terrestrial signals to multiple users via a single optical fibre. It can also be amplified. Highlights- High output level, ideal for community systems with up to 64 splits- Compatible with GPON installations- Low losses- Optimised electronics- Very compact in dimensions (137x126x45mm) low weight- For indoor use- Powered by an external power supply, via the power input (F connector)- 100% European design, quality and manufacture Features- SC/APC connector for optical components- F connector for RF input- Highly shielded zamak housing- Wall and pole mounting- Power supply and adapter cable included- LED signal status indicator Physical data- Net weight: 400 g- Gross weight: 641 g- Width: 137 mm- Height: 123 mm- Depth: 45 mm- Main product weight: 400 g

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

