

Item no.: 389544

## OSK10S - Shielded fibre optic cable 10 m with 2 x FCPC connectors

## from **24,07 EUR**

Item no.: 389544 shipping weight: 0.30 kg Manufacturer: Televes



## Product Description

Pre-assembled single-mode (SM) fibre optic patch cable with FC/UPC connectors for connecting units in an optical SAT IF installation. Equipped with a shielded stainless steel tube around the optical fibre as well as an aramid braid strain relief and a UV-resistant LSFH jacket.ldeal for outdoor use and underground installation as it has been specially developed to withstand adverse weather conditions.Highlights- Low attenuation- Aramid fibre protection and flexible stainless steel conduit- Outstanding durability: the flexible stainless steel shielding ensures excellent mechanical resistance and protects the fibre against all types of physical stress: impacts, pulling, kicks...- Glass fibre type G.657A2- LSFH cover with UV protection, grey- FC/UPC connectors- Available in various lengthsTechnical dataFibre types - Single mode (ITU-T-G.657A2)## - OS1Fibre core diameter- ?m Pibre cladding diameter on fibre- ?m 250Cable structure- Fixed coreFibre structure diameter - mm 0,8Outer sheath diameter- mm 3Outer sheath material - LSFHProtective gel - NoAttenuation 1310nm - dB/km < 0.4Attenuation 1490nm - dB/km < 0.4Attenuation 1550nm - dB/km < 0.3Insertion loss connection 1 - dB < 0.3Insertion loss connection 2 - dB < 0.3Return loss connection 1 - dB > 50Return loss connection 2 - dB > 50Optical port 1 type - FCGround joint type (optical port 2) - UPCShort pull - N 440Strength increase element - Aramid fibres and flexible stainless steel tubeShort breakage (@ 100mm) - N 1000Minimum propagation speed - mm 30Operating temperature- °C -20 ... 70Physical dataNet weight:- 148gGross weight:- 148gWidth:- 9mmHeight:- 10.114mmDepth:- 9mmMain product weight:- 148g

Specifications

Scan this QR code to view the product All details, up-to-date

All details, up-to-date prices and availability

