

Item no.: 389685

OSM75SCAPC - shielded fibre optic cable 75 m with 2 x SCAPC connectors

from **103,79 EUR**

Item no.: 389685
shipping weight: 2.30 kg
Manufacturer: Teledes



Product Description

Pre-assembled single-mode (SM) fibre optic patch cable with SC/APC connections. Equipped with a shielded stainless steel tube around the optical fibre as well as an aramid braid strain relief and a UV-resistant LSFH jacket. Ideal for outdoor use and underground installation as it has been specially developed to withstand adverse weather conditions and rodent attacks. Supplied in individual packaging. Item no. OSM75SCAPC Length: 75 m Product data- Ref.No.: 236138- EAN13: 8424450255919 Highlights- Low attenuation- Aramid fibre protection and flexible stainless steel conduit- Outstanding durability: the flexible stainless steel shielding provides excellent mechanical resistance and protects the fibre against all types of physical stress: shocks, pulling, kicks, bites... Technical specifications- Fibre types: Single mode (ITU-T-G.657A2)- ##: OS1- Fibre core diameter: 9- Fibre cladding diameter: 125- Fibre cladding diameter: 250- Cable structure: Fixed core- Fibre structure diameter: 0.8- Outer sheath diameter: 0.8- Outer sheath material: LSFH- Protection gel: No- Attenuation 1310nm: 0.4- Attenuation 1490nm: 0.4- Attenuation 1550nm: 0.3- Insertion loss port 1: 0.3- Insertion loss port 2: 0.3- Return loss port 1: 50- Return loss port 2: 50- Optical port 1 type: SC- Section type (Optical port 1): APC- Optical port 2 type: SC- Section type (Optical port 2): APC- Short tensile strength: N 440- Strengthening element: aramid fibres and flexible stainless steel tube- Short breakage (@100mm): N 1000- Minimum propagation speed: 30- Operating temperature: °C -20 ... 70 Physical data- Net weight: 1,980g- Gross weight: 2,000g

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

