

Item no.: 392454

UVC-G5-PTZ - All-weather camera, PoE+, 2k, night vision

from **283,33 EUR**

Item no.: 392454
 shipping weight: 0.70 kg
 Manufacturer: Ubiquiti



Product Description

Compact, all-weather camera with ultra-low latency pan-tilt-zoom control and versatile mounting options. 2K (4MP) video resolution 2x optical zoom 20 m IR night vision AI event detection and automatic people tracking Audio recording with integrated microphone Integrated LED spotlight for night vision in colour Connection and power supply via PoE+ Weatherproof (outdoor) Technical data Mechanical Dimensions Without bracket: Ø90 x 152.5 mm (Ø3.5 x 6"), With bracket: 90 x 94 x 179.5 mm (3.5 x 3.7 x 7") Weight Without bracket: 580 g (1.3 lb), With bracket: 650 g (1.4 lb) Housing material Aluminium alloy, polycarbonate Bracket material Wall bracket: polycarbonate, pole bracket: aluminium alloy Pole bracket diameter 38-50mm (1.5-2") on the outside diameter of the pipe Weather resistance IP66 Resistance IK04 Optics Sensor 5MP 1/2.7" CMOS Lens F 3.42-6.85 mm; f/1.85-f/2.4 Angle of view 16:9 wide angle: H: 99.7°, V: 51.9°, T: 121°, 16:9 telephoto: H: 45.5°, V: 25.4°, D: 52.4° Night mode Built-in IR and white LED illumination with IR cut filter IR distance 20m IR restriction Distance from top/side ?60 cm Video Resolution 4MP 2688 x 1512 (16:9) Max. Frame rate 30FPS System Network interface 10/100MbE RJ45 connection Max. Power consumption 14W Power supply method PoE+ Supported voltage range 37-57VDC LEDs R/G/B/W: Connection, Activity, Floodlight: 400 lm Button Factory reset Mounting Wall, pole mounting (included), pipe adapter, surface, ceiling, pendant, corner mounting (optional, Operating temperature -30 to 45° C (-22 to 113° F) Humidity 0 to 90% non-condensing Certifications FCC, IC, CE Audio Microphone Yes (can be disabled) Software Web application UniFi Protect Mobile app UniFi Protect iOS™ and Android™

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

