

Item no.: 389757

## SK6FPLUS-B - Coaxial cable A Staku 1.04.6 mm, triple shielded, aluminium 250 m dispenser

from **52,46 EUR**

Item no.: 389757  
shipping weight: 14.00 kg  
Manufacturer: Televes



### Product Description

SK6Fplus coaxial cable, white Euroclass Eca, shielding Class A+ (Rollbox®)RG-6 coaxial cable with steel copper inner conductor.100 dB typ. Shielding rating, triple shielded and coverage >60%.Highlights- Steel copper inner conductor and aluminium braiding- Class A+- EU fire protection class EcaFeatures- Colour: white, PVC jacket- 75 Ohm impedance- 250 m Rollbox®Good to knowRollbox®: practical and environmentally friendly packaging for the cable professionalThe Rollbox® is a practical packaging concept developed to save installation time and allow cables to be unrolled smoothly and quickly. In addition, transporting the cable is effortless thanks to the integrated, reinforced handles. In addition, the packaging remains intact as it does not need to be opened to unroll the cable.The Rollbox® is also a responsible and environmentally friendly alternative thanks to its production from recycled, ecological cardboard and screen printing with biological ink.3-triple shielded class A+ coaxial cablesDue to the triple shielding, these cables offer the highest level of protection against interference radiation, e.g. caused by LTE/4G signals.Fulfils shielding class A+ according to EN 50117:- At 5 MHz - 30 MHz => TI < 2.5 m²/m- At 5 MHz - 1000 MHz => SA > 95 dB- At 1000 MHz - 2000 MHz => SA > 85 dB- At 2000 MHz - 3000 MHz => SA > 75 dBThe transfer impedance determines how effective the shielding is at low frequencies and the shielding attenuation is defined in the frequency range of 30 MHz-3000 MHz.

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

