

Item no.: 389369

## SAV25FZ - 2-way distributor 5-2400 MHz VD: 4dB

from **14,90 EUR**

Item no.: 389369  
 shipping weight: 0.10 kg  
 Manufacturer: Televes



### Product Description

2-way distributor with F connectors, for SMATV installations. Due to the reduced size of the electronic components, it has low feed-through losses, which improves its electrical behaviour. In addition, its zamak housing provides good shielding. It is designed for indoor installation, for wall, rack plate or standard DIN rail mounting. Highlights- Mounting flexibility: can be screwed to the wall, installed on mounting plates with nuts on the connections or on a standard DIN rail (with adapter no. 519901)- Convenient screwing of the cable thanks to an inclination angle of the F connectors of 10° to the installation wall- Space optimisation in enclosures and cabinets: the inputs and outputs are always on the same side- Better organisation of the installation: Allows cabling to pass through the rear- The F-series elements can be connected together with the earthing screw, so that only a single earthing cable is required- The signal level is maintained in the sockets even with long cables, thanks to a better flatness response- Outstanding reliability: robotised manufacturing with new generation micro-components- 100% European design, quality and manufacture Features- Low through loss- Good shielding (class A), made of zamak- F connector with longer thread, to facilitate and secure installation on a mounting plate- Indoor installation- Earthing screw included- DC feed-through from the outputs to the input Technical data Frequency range- MHz 5 ... 2400 Number of outputs- 2 Inputs/frequency band- TERR Pass-through attenuation - dB 5 Decoupling - dB > 20 Inputs/frequency band- SAT Feed-through attenuation - dB 4 Decoupling - dB > 20 Connectors - F-socket Voltage Max.- V 24 Max. Current consumption - mA 350 DC pass-through- Off.? On. Physical data Net weight:- 59g Gross weight:- 63g Width:- 74mm Height:- 54mm Depth:- 18mm Main product weight:- 59g

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

