

Item no.: 390024

VST20 - SAT - post amplifier gain 20 dB

from **50,83 EUR**

Item no.: 390024
shipping weight: 0.20 kg
Manufacturer: Televes



Product Description

Inline amplifier Ter./Sat. Terrestrial pass-through inline amplifier for satellite and terrestrial. Provides amplification of the SAT signal with low losses in the terrestrial range. Maximum current flow between output and input of 0.5 A. Highlights- SAT amplification: 22 dB, with high input level- Ter amplification: -2.5 dB- High shielding due to cast housing- Low noise figure- Current flow between output and input Features- F connections- Indoor or outdoor mounting (with housing Ref. 4163)- Current flow between output and input Technical specifications Number of inputs - 1 Number of outputs - 1 Frequency band - VHF Frequency range - MHz 47 ... 230 Gain - dB --Throughput attenuation - dB 2.5 Output voltage DIN VDE0855/12 - dB?V -- Noise figure - dB --Frequency band - UHF Frequency range - MHz 470 ... 862 Gain - dB --Vapour transmission - dB 2.5 Output voltage DIN VDE0855/12 - dB?V -- Noise figure - dB -- Frequency band - SAT Frequency range - MHz 950 ... 2150 Gain - dB 20 Feed-through attenuation - dB --Output voltage DIN VDE0855/12 - dB?V 112.5 Noise figure - dB 5.5 Power supply - Vdc 12 ... 18 Current consumption - mA 60 DC pass-through - SAT? On. Max. Current forward - mA 500

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

