

Item no.: 390022

## SPU88T - Octo-Switch feed system, 8 TN, feed 40 mm

from **95,78 EUR**

Item no.: 390022  
shipping weight: 0.60 kg  
Manufacturer: Teledesic



### Product Description

Octo LNB with eight universal outputs, each with all 4 polarities (HL, HH, VL, VH). Supplied in individual sales packaging. Highlights- Unobtrusive and small housing- High gain- Low noise figure- Excellent linearity and equalisation- Very good differentiation between the polarities- IP-protected housing (IP66)- Can be used under extreme temperature conditions Features- Very light - Compatible with all four polarities - Very light Very lightweight- Compatible with 40 mm feed holder- Low power consumption- Power supply either via the receiver or the multiswitch- Easy connection- Multifield-compatible solution Specification- Frequency range GHz 10,7 ... 12.75- Horizontal reception level Vdc 15.5 ... 20- Receive level Vertical Vdc 11 ... 14.5- Output frequency range MHz 950 ... 2150- Frequency Oscillator 0KHz GHz 9.75- Frequency Oscillator 22KHz GHz 10.6- Gain dB 60- Noise dB 0.3- Stability L.O. MHz -1.5 ... 1.5- Decoupling dB > 20- Phase noise (@10 KHz) dBc -75- Power supply Vdc 11 ... 20- Max. Current consumption mA 255- Impedance ? 75- Connectors F-socket- Ø LNB holder mm 40- Operating temperature °C -30 ... 55 Physical data- Net weight: 580 g- Gross weight: 580 g- Width: 141 mm- Height: 100 mm- Depth: 74 mm- Main product weight: 352 g Packaging- Carton 1 pc.- Carton 30 pcs.- Pallet 540 pcs.

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

