

Item no.: F-SC311-21

F-SC311-21 - Mini Bullet IP Camera

from **141,28 EUR**

Item no.: F-SC311-21
shipping weight: 0.10 kg
Manufacturer: Four-Faith



Product Description

F-SC311-21 - Mini Bullet IP Camera

F-SC311 is a very small bullet camera with two different color appearances (white or metal gray cover). It provides 2 MP sensors and a fixed lens. It can be customized to add multiple IoT interfaces.

Camera

- Image sensor: 1/2.8" progressive scan CMOS
- Resolution: 2 MP
- Min. illumination: Color: 0.002 Lux (at) F1.2; B/W: 0 Lux with IR on
- WDR: Super WDR up to 140 dB
- Lens: Fixed lens: 2.8 mm (at) F2.0/3.2 mm (at) F2.2/3.6 mm (at) F2.2/4 mm (at) F2.2/6 mm (at) F2.2
- Mount: M12, F14
- IR distance: Up to 50 m
- Day & night: ICR filter auto switch

Video

- Max. image resolution: 1920 x 1080
- Primary stream: 30 fps (at) (1920 x 1080, 1280 x 960, 1280 x 720, 704 x 576)
- Secondary stream: 30 fps (at) (704 x 576, 640 x 480, 640 x 360, 352 x 288, 320 x 240, 320 x 192, 320 x 176)
- Tertiary stream: 30 fps (at) (1920 x 1080, 1280 x 720, 704 x 576, 640 x 480, 640 x 360, 320 x 240, 320 x 192, 320 x 176)
- Video compression: H.265 (HEVC)/H.264/MJPEG
- Bit rate: 16 Kbps ~ 16 Mbps (CBR/VBR adjustable)
- Image setting: Brightness/contrast/saturation/sharpness

Network

- Ethernet network storage: 1x RJ45 10M/100M Ethernet port; NAS (supports NFS, SMB/CIFS)
- Protocol: IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DHCP, NTP, SNMP, NFS, CIFS

System

- Storage: Supports microSD/SDHC/SDXC card local storage, up to 128 G
- Advanced function: Motion detection, privacy masking, backlight compensation, HLC, 2D DNR, 3D DNR, ROI, anti-fog, white balance, EIS, IP address filtering
- Event trigger: Motion detection, network disconnection, external input, etc.
- Event action: FTP upload/SMTP upload/SD card record
- Video analysis: Region entrance, region exiting, advanced motion detection, tamper detection, line crossing, loitering, human detection, people counting, object left, object removed (*in development)
- System compatibility: ONVIF Profile S

General

- Working temperature: -40°C ~ 60°C
- Working humidity: 0 ~ 90% (non-condensing)
- Power supply: PoE (802.3af)
- Power consumption: 3 W max.; 6 W max. (with IR on)
- Weatherproof: Up to IP67-rated for weather-resistant performance
- Weight: 600 g (junction box version); 410 g (cable out version)
- Dimensions: F67 x 190 mm

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

