

Item no.: 391314

XV2-21X0A00-EU - Cambium Networks XV2-21X Indoor Wi-Fi 6 Access Point (EU)

from **430,74 EUR**

Item no.: 391314
shipping weight: 0.80 kg
Manufacturer: MikroTik



Product Description

Product Description Cambium Networks XV2-21X Wi-Fi 6 Indoor Access Point offers an attractive price/performance ratio for any market. The XV2-21X can be adopted and managed by any of Cambium Networks management systems, cnMaestro™ Cloud, cnMaestro™ X, cnMaestro™ onpremises or Swift App-based management. Choose the type of management you need and change it at any time. Unlike other low-cost access points, the XV2-21X is not locked into a single management choice. Designed for quick installation The XV2-21X offers multiple installation methods included in the same shipping box. Mount the AP to a ceiling tile with the included steel plate, mount it to an existing junction box with 83mm holes, mount the AP with a 36mm, 24mm and 14mm T-rail, or simply mount it to any flat surface with the included wall anchors. No additional brackets are required. Free online tool for designing your Cambium Wi-Fi network Key features- Dual Radio Wi-Fi 6- 5 GHz (2x2), 2.4GHz (2x2)- 1 GbE RJ45- Managed by cnMaestro and/or Swift Technical parameters Wireless features- Wireless frequency: 2.4 + 5 GHz (dual band)- WiFi standards: 802.11ac, 802.11ax - wave2, 802.11n, 802.11a, 802.11b/g- MU-MIMO: Yes- Transmission speed - 5GHz [Mb/s]: 2402- Transmission speed - 2.4GHz [Mb/s]: 574- Transmission power 2.4GHz [dBm]: 32- Transmission power 5GHz [dBm]: 33- Security: WPA, WPA2, WPA3- 2.4GHz MIMO: 2 x 2- 5GHz MIMO: 2 x 2- Antenna type: Built-in- Roaming: Yes Connections and interfaces- LAN speed: (1) 10/100/1000Mbps- Gigabit LAN: Yes Power supply- Power over Ethernet: 802.3af- PoE type: PoE-In (only)- Max. Power consumption [W]: 11 Physical characteristics- Purpose: Indoor- Operating temperature [°C]: 0 to 50- Weight [g]: 476- Width [mm]: 155- Height [mm]: 37- Depth [mm]: 155 Software- Operating mode: Access point- Management: Web management, Cambium cnMaestro Cloud- IPv6 support: Yes- Default IP address: 192.168.0.1, Dynamic from DHCP- Default login and password: admin / admin

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

