

Item no.: 389611

OSK24-250/2000 - FK24 Opt.cab.24fibres-2 km LSFH Dca Dca (G657A2) 250

from **11,19 EUR**

Item no.: 389611
shipping weight: 60.00 kg
Manufacturer: Teledesic



Product Description

24-fibre cable with UV-resistant LSFH sheath for indoor and outdoor installation. Divided into 6 micro-modules of 4 fibres each, each with its own LSFH sheath and different colour. This enables better organisation and simplifies identification. Reference 231614 is supplied by the metre. Highlights - EU fire protection class Dca-s2,d2,a1 - Low attenuation - Distributed in fibre micro-modules - Gel for protection against water - Good increase in structural strength with aramid fibres. Maintains tensile strength without an additional central guide wire for resistance. - Glass fibre type 9/125, ITU-T G.657.A2 - Equipped with a core guide wire for resistance - UV-resistant LSFH sheath, orange Specification - Euroclass Dca - Euroclass: Smoke development s2 - Euroclass: Dripping of particles d2 - Euroclass: Acidity a1 - Fibre type monomode (ITU-T-G.657A2) - Diameter fibre core 9 - Diameter fibre cladding 125 - Cladding diameter on fibre 250 - Cable structure fixed core - Fibre structure diameter mm 0.85 - Outer cladding diameter mm 7.6 - Material outer cladding LSFH, UV-resistant - Gel for protection Yes - Attenuation 1310nm dB/km < 0.4 - Attenuation 1490nm dB/km < 0.4 - Attenuation 1550nm dB/km < 0.3 - Short tensile force N 1000 - Strength increase element aramid fibres - Short break (@100mm) N 1000 - Long break (@100mm) N 750 - Minimum propagation velocity mm 76 - Operating temperature °C -5 ... 60

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

