

Item no.: 394634

## 64282 - 3 port USB 5 Gbps hub Gigabit LAN with USB Type-C or USB Type-A connection

from **36,58 EUR**

Item no.: 394634  
shipping weight: 0.10 kg  
Manufacturer: Delock



### Product Description

Description This sturdy USB hub by Delock in a metal housing is connected to a computer, notebook or mobile device via the USB Type-A or USB-C™ port. Up to 3 USB devices can be connected to the hub. In addition, the hub with integrated RJ45 Gigabit LAN connection expands a PC or notebook with a network interface. Extensive connection options Thanks to the specially designed adapter, the Delock hub can also be quickly and easily connected to the USB type-A socket. This means it can be easily connected to new devices with a USB Type-C™ socket and older devices that only have a USB Type-A connection. The adapter is located directly on the cable and therefore cannot get lost. Small, stable and handy The Delock hub is particularly suitable for mobile use due to its small dimensions and stable housing. It can be easily stowed in a bag together with a notebook or tablet and can be used immediately when needed. Technical data- Function: Plug & Play- Supported operating system: - Chrome OS Surface Pro 7 Windows 10 32-bit Windows 10 64-bit iPad Pro (3rd generation) or higher iPad Air AirPort (3rd generation) or higher iPad AirPort (3rd generation) or higher iPad AirPort (3rd generation) or higher iPad Air (4th Generation) or higher Windows 11 Mac OS 12.4 or higher Android 13.0 or higher Linux Kernel 5.19 or higher- Port 1: 1 x USB 5 Gbps USB Type-C™ plug- Port 2: 3 x USB 5 Gbps Type-A socket- Port 3: 1 x Gigabit LAN RJ45 socket- Adapter: 1 x USB 5 Gbps USB Type-C™ socket 1 x USB 5 Gbps Type-A plug- Chipset: Genesys Logic GL3510, Realtek RTL8153- Data transfer rates: Ethernet up to 10 Mbps (half/full duplex) Fast Ethernet up to 100 Mbps (half/full duplex) Gigabit Ethernet up to 1000 Mbps (half/full duplex)- Compatible with: IEEE 802.3: 10BASE-T IEEE 802.3u: 100BASE-TX IEEE 802.3ab: 1000BASE-T- Supports Auto MDI-X (automatic detection of standard or crossover network cables)- Supports Wake On LAN (WOL)- Supports IEEE 802.3az (Energy Efficient Ethernet)- Supports IEEE 802.1Q Virtual LAN (VLAN)- Supports Full Duplex with IEEE 802.3x Flow Control and Half Duplex operation with Back-pressure- Supports 4k Jumbo Frames- Robust metal housing- Dimensions (LxWxH): approx. 86 x 30 x 17 mm- Cable length incl. connection: approx. 20 cm- Colour: grey- Plug & Play System requirements- Android 13.0 or higher- Chrome OS- Linux Kernel 5.19 or higher- Mac OS 12.4 or higher- Windows 10/10-64/11- iPad Air (4. Generation) or higher- iPad Pro (3rd generation) or higher- Surface Pro 7- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port or- One free USB Type-A port

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

