

Item no.: 391801 DEC2770 - OPNsense® rack security application, 7x 2.5GbE

from 1.462,15 EUR

Item no.: 391801 shipping weight: 3.00 kg Manufacturer: Deciso



Product Description

DEC2770 - OPNsense® Rack Security ApplianceUnrivalled in its classUp to 10 Gigabit performance in a 1U rack. Fully equipped, ideal for SMEs and branch offices. With up to 7x 2.5GbE! (DEC2770)Software- Preinstalled software OPNsense®- Licence Open Source + 1 year free Business EditionHardware Specifications- Typical Applications Firewall / Routing, VPN, IDPS-SFP+ Ports [10Gbps] 2 - 2.5 GbE RJ45 Ports [100/100//2500Mbps] 7 - USB 3.0 Ports 1 - Console Port 1 - Internal Storage 256GB M.2Solid State Flash-Memory 8GB DDR4- CPU Cores 4 (max frequency 2.2Ghz)- Virtual Interfaces (802.1q VLANS)1 4093 System Performance- Firewall Throughput 10Gbps - Firewall Packets Per Second 830Kpps - Firewall Port to Port Throughput 8.5Gbps- Firewall Port to Port Packets Per Second 719000- Concurrent Sessions 7000000 - Firewall Latency (average) 150us-Firewall Policies (Recommended Maximum)1 10000- IPsec VPN Throughput (AES256GCM16) 1.2Gbps- IPsec VPN Packet Per Second (AES256GCM16) 107Kpps- OpeVPN SSL Throughput (AES256GCM16) 500Mbps- OpenVPN Packet Per Second (AES256GCM16) 42Kpps- Threat Protection Throughput Packet Per Second (AES256GCM16) Threat Protection Throughput Packet Per Second 850Kpps- Threat Protection Throughput -1Gpbs - High Availability with State Synchronisation Requires Two- DimensionsHeight x Width x Length (inches) 1.75 x 19 x 9.53 (8.43 excl. panel) - Form Factor 19" Rackmountable- Weight (appliance only) 2.75KgEnvironment- Power Requirements 100-240VAC, 50-60Hz- Maximum Current (AC) 0.8A- Power Consumption (Typical) 20W- Heat Dissipation (Typical) 68.3 BTU/hr- Operating Temperature 0 to +45°C- Storage Temperature -20 to +70°C- Humidity 10-90% non-condensingRegulatory Compliance- FCC part 15 Class A, CE, Rohs

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

