

Item no.: 394902

47042 - Delock PCI Express x16 card removable frame for 2 x M.2 NVMe SSD - Bifurcation

from **177,57 EUR**

Item no.: 394902
shipping weight: 0.50 kg
Manufacturer: Delock



Product Description

This removable rack by Delock can be installed in a PC slot of the computer and provides two M.2 slots in 2280, 2260, 2242 or 2230 format. Quick replacement of SSDs. The special mechanism allows the SSDs to be replaced quickly and easily. For example, data backups can be removed and stored in a safe place. Slot with lock and suspension. The removable frame has a key lock to ensure that only authorised persons can remove the drive. The sturdy metal carrier has springs on the top and bottom that absorb vibrations and therefore also support use in mobile devices. Note: Care must be taken to ensure that the slot is fully inserted, otherwise no connection to the SSD can be established. Without PCIe bifurcation, only the first M.2 slot of the card can be used. Technical data: Connectors: PCIe card: 1 x PCI Express x16, V4.02 x M.2 Key M Slot. M.2 slot: 1 x M.2 Key M connector. 1 x M.2 Key M Slot. Interface: PCIe / NVMe. Supports M.2 modules in 2280, 2260, 2242 and 2230 format with Key M or Key B+M on PCIe basis. Maximum height of components on the module: 1.5 mm, use of double-sided modules possible. 2 x fans. 2 x LED display. Bootable, from UEFI version 2.3.1. M.2 Metal slot. Supports NVM Express (NVMe). Supports S.M.A.R.T. - Operating temperature: -40 °C ~ 85 °C. System requirements: Linux Kernel 6.2 or higher - Windows 10/10-64/11 - Windows Server 2022 - PC with one free PCI Express x16 / x32 slot. Package contents: Removable frame with 2 x M.2 slot - Heat sink - 2 x screw IM 2.0 x 4.0 mm, head 5.0 mm - 2 x keys - Operating instructions

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

