

Item no.: 395251

## 90605 - Wearable barcode scanner 1D and 2D with 2.4 GHz or Bluetooth - for hands-free scanning

## from 114,02 EUR

Item no.: 395251 shipping weight: 0.10 kg Manufacturer: Delock



## Product Description

This barcode scanner by Delock can be connected wirelessly to a PC, notebook or directly to a mobile phone or tablet. All common 1D and 2D barcode types can be scanned precisely even from a long distance. The scanner also recognises barcodes shown on displays and monitors. Automatic adaptation to ambient brightness The scanner automatically adapts to the ambient brightness and captures up to 100 scans per second under optimum lighting conditions. When the ambient brightness is low, the barcode is illuminated by an additional white LED and can therefore also be used in poor lighting conditions. PracticalThis portable scanner can be conveniently attached to the glove using a snap-in mechanism, leaving the wearer's hands free to hold a box, for example. Transmission via Bluetooth, USB or 2.4 GHzThe scanned barcodes are transmitted either via Bluetooth directly to the Bluetooth-enabled output device or via the 2.4 GHz frequency band using the USB dongle supplied. Alternatively, the scanner can be connected to the computer with the enclosed USB cable. NoteThe scanner can also be used without a glove. Not suitable for Swiss QR codes. Technical data- Connection: 1 x USB Type-C™ socket- Decoding chip: ARM Cortex 32 Bit- Battery: Li-Polymer 380 mAh- Resolution: 1280 x 800- Trigger: Push button- Reading distance: approx. 30 mm to 300 mm- Reading accuracy: 4 mil- Operating time: approx. 8 hours for 2D, 12 hours for 1D- Range:Indoor range: up to 10 mOutdoor range: up to 10 m- Charging time: approx. 2 hours- Internal memory: 16 MB- LED display for charging status, Bluetooth connection and power- Light colour: visible LED red- Compensation light: LED white- Sensor: CMOS image sensor- Scan rate: up to 100 scans per second- Tilt angle: 360°- Ambient brightness: max. 10000 lux- Input voltage: 3.3 V- Power consumption: Operation: max. 100 mA- Standby: max. 30 mA- Operating temperature: -10°C ~ 60°C- Storage temperature: -40°C ~ 70°C- Relative humidity: 5 - 90 % (non-condensing)- Colour: black- Weight: approx. 40 g- Dimensions (

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

