

Item no.: 387751

## SFP-1GLHXLC - SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission

from **699,67 EUR**

Item no.: 387751  
shipping weight: 0.10 kg  
Manufacturer: MOXA



### Product Description

Moxa's small form-factor pluggable transceiver (SFP) Ethernet fibre optic modules for Gigabit Ethernet cover a wide range of communication distances. SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature Ethernet interface- Ports: 1- Connectors: duplex LC connector, simplex LC connector (WDM type only), fibre optic- Fibre optic: Typical distance: To achieve the typical distance of the specified fibre optic transceiver, please observe the - Formula: Link budget(dB) > Dispersion loss(dB) + Total loss(dB) Performance parameters- Power consumption: Max. 1 W Environmental limits- Operating temperature: 0 to 60°C (32 to 140°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications-Safety: UL 62368-1, IEC 62368-1, IEC 60825-1-EMC: EN 55032/35-EMI: FCC 15B Test Report, ICES-003: 2020 Edition 7-EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V-IEC 61000-4-8 PFMF: 1 A/m at 50 Hz, IEC 61000-4-11 Voltage dips and interruptions-Maritime: DNV

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

