

Item no.: 389860

## OSK2I-300 - Optical cable, 2 fibres, singlemode LSFH Dca, f. Indoor 300m

from **8,65 EUR**

Item no.: 389860  
shipping weight: 5.00 kg  
Manufacturer: Teledesic



### Product Description

Optical cable with 2-fibre (single-mode) with LSFH sheath for internal installation. Each fibre has its own LSFH sheath and is marked with a specific colour. This provides a better overview and makes identification easier. Highlights- Low attenuation- Contains aramid fibres to reinforce the structure- EU fire protection class Dca- 9/125 fibre, ITU-T G.657.A2- Coating diameter adapted to the fibre: 900 µm- LSFH sheath, colour orange Specification- Euroclass Dca- Euroclass: Smoke development s2- Euroclass: Dripping of particles d0- Euroclass: Acidity a1- Fibre types monomode (ITU-T-G.657A2)- Diameter fibre core 9 µm- Diameter fibre cladding 125 µm- Cladding diameter on fibre 250 µm- Cable structure fixed core- Fibre structure diameter mm 0.9- Outer cladding diameter mm 3.5- Material outer cladding LSFH- Gel for protection No- Attenuation 1310nm dB/km < 0.4- Attenuation 1490nm dB/km < 0.4- Attenuation 1550nm dB/km < 0.3- Short tensile strength N 500- Strength increase element aramid fibres- Short breakage (@100mm) N 500- Minimum propagation velocity mm 17.5- Operating temperature °C -20 ... 7-0

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

