

Item no.: 391310

MX-EX1028PXA-0 - cnMatrix PoE switch

from **1.007,84 EUR**

Item no.: 391310
shipping weight: 4.70 kg
Manufacturer: Cambium Networks



Product Description

The Cambium Networks EX1028-P Gigabit L2 PoE switch is equipped with 24 metallic PoE+ 1G ports and 4x 1G SFP uplink ports. The switch has an RJ-45 console connection. The switch is powered by an in-built AC power supply unit and the PoE budget switch delivers 200 W. The switch is a 19-inch rackmount with a height of 1U and a depth of only 250 mm. The switch is designed as an access switch with PoE power supply. Main features- Manageable Gigabit L2 PoE+ switch- Main features - Static route, inter-VLAN routing- 19-inch rackmount with fixed ports- 4x 1GE SFP uplink ports- 10/100/1000 Mbps port with PoE+ support- PoE power: 200 W- Built-in AC power supply- Forwarding power: 120 Mbps- Switching capacity: 56 Gbps- Memory (SDRAM): 512 MBThe device can be managed via the web interface or the cnMaestro™ cloud element management system to simplify deployment, monitoring and updates. Connectors and interfaces- LAN speed: (24) 10/100/1000 Mbit/s- Optical interfaces: (4) 1000 Mbit/s- Serial connection: RJ45- USB ports 2.0: 1Power- Power type: Mains power (230 V)- PoE type: PoE-Out (only)- PoE-Out standards: 802.3af, 802.3at- PoE-Out ports: 24- PoE budget [W]: 200- Max. Power consumption [W]: 25- Power supply plug via/terminal: 230 V ACFeatures- Design: Rackmount- Fan: (2) 40 x 40 mm- Housing design: Metal- Buttons: Reset- Operating temperature [°C]: 0 to 50- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 250General- Switching capacity [Gbit/s]: 56- MAC address table: 16000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 120SoftwareWeb management: YesManagement: Web management, Cambium cnMaestro Cloud, SSH, TelnetFunctions: VLAN, QoS, DHCP snooping

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

