

Item no.: 392264

SX3016F - JetStream switch

from **626,69 EUR**

Item no.: 392264
shipping weight: 4.00 kg
Manufacturer: TP-LINK



Product Description

TL-SX3016F is an optical switch for a 19" rack with a height of 1U, which provides 16x 1G/10G SFP+ ports, two console ports (RJ45 and microUSB) and two redundant built-in power sources to increase the reliability of the entire switch. For management and monitoring, it is possible to use shared access via a web interface and protocols such as CLI, SNMP, RMO as well as centralised cloud management and a software controller. The Omada hardware controller (OC200 / OC300) is also supported. Switch with many functions. The switch offers high-performance routing based on IP, MAC, TCP or UDP. All this in combination with advanced security strategies (IP-MAC port binding, ACL, Port Security, DoS Defend, Storm control, DHCP Snooping, 802.1X, Radius Authentication ...). With all these advanced features, the Gigabit L2 + JetStream switch is the ideal choice for SMB solutions. Scope of delivery- Device- (2) power cables- 19" rack bracketsConnections and interfaces- Optical interfaces: (16) 1G/10Gbps- Serial port: micro USB, RJ45Power supply- Power type: Mains power (230V)- Redundant power supply: Yes- Max. Power consumption [W]: 33- Power supply via plug/terminal: 230V ACPhysical properties- Design: Rackmount- Fan: (1) 40 x 40 mm- Housing design: Metal- Operating temperature [°C]: 0 to 45- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 220General- Switching capacity [Gbps]: 320- MAC address table: 32000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 238.1Software- Web management: Yes- Management: Web management, Omada controller, SSH, Telnet- Functions: VLAN, QoS, DHCP snoopingDefault IP address: 192.168.0.1- Default login and password: admin / admin

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

