

Item no.: 392259

## SG3452P - JetStream PoE switch

from **659,36 EUR**

Item no.: 392259  
shipping weight: 6.90 kg  
Manufacturer: TP-LINK



### Product Description

The Jetstream TL-SG3452P PoE switch from TP-Link is a manageable L2+ switch with PoE function that contains 48 Gigabit LAN ports with 802.3af/at PoE function and a further 4 Gigabit SFP ports. The switch has a total PoE budget for power supply via a 384 W cable, the switch can be installed in a 19" rack and 3 Venitatoros provide cooling from the side. Important features- 384 W PoE budget: 48 x 802.3af/at-compliant PoE+ ports- 48x Gigabit RJ45 ports and 4x Gigabit SFP slots provide high-speed connections.- Integration with Omada SDN: Zero-touch provisioning, centralised cloud management and intelligent monitoring- Centralised management: Cloud access and Omada app for easy management- Static routing - Helps route internal traffic for more efficient use of network resources.- Robust security strategies: IP-MAC Port Binding, ACL, Port Security, DoS Defend, Storm control, DHCP Snooping, 802.1X, Radius Authentication, and much more- Optimise voice and video applications: L2 / L3 / L4 QoS and IGMP Snooping- Independent management: Web, CLI (console port, Telnet, SSH), SNMP, RMON and Dual Image provide powerful management functionsPackage contents- Device- Power cable- 19" rack bracketsTechnical parametersConnectors and interfaces- LAN speed: (48) 10/100/1000 Mbit/s- Optical interfaces: (4) 1000 Mbit/s- Serial connection: Micro-USB, RJ45Power supply- Power type: Mains power (230 V)- PoE type: PoE-Out (only)- PoE-Out standards: 802.3af, 802.3at- PoE-Out ports: 48- PoE budget [W]: 384- Max. Power consumption [W]: 53- Power supply via plug/terminal: 230 V ACPhysical properties- Design: Rackmount- Fan: (3) 40 x 40 mm- Housing design: Metal- Buttons: Reset- Operating temperature [°C]: 0 to 40- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 330General- Switching capacity [Gbit/s]: 104- MAC address table: 16000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 77.4Software- Web management: Yes- Management: VLAN, QoS, DHCP snooping- Default IP address: 192.168.0.1- Default login and password: admin / admin

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

