

Item no.: 392292

SG3428X-M2 - TL- JetStream switch

from 494,02 EUR

Item no.: 392292 shipping weight: 3.20 kg Manufacturer: TP-LINK



Product Description

The switch offers 24x 100/1000/2500 Mbps LAN ports for clients and an additional 4x optical SFP+ ports, which primarily serve as uplinks with a total switching capacity of 200 Gbps. For management and monitoring, it is possible to use general access via a web interface and protocols, e.g. CLI, SNMP, RMO, but also centralised cloud management and software controllers. Omada hardware controllers (OC200/OC300) are also supported. Switch with many functions The switch offers high-performance routing based on IP, MAC, TCP or UDP. All this combined with advanced security strategies (IP-MAC port binding, ACL, port security, DoS Defend, Storm control, DHCP Snooping, 802.1X, Radius Authentication.....). With all these advanced features, the Gigabit L2+ JetStream Switch is the ideal choice for SMB networking solutions. Omada ControllerThe Omada Software Defined Networking (SDN) platform integrates network devices, including access points, switches, gateway routers and provides 100% centralised management in the cloud. Omada creates a highly scalable network including control from a single interface. Provides seamless wireless and wired connectivity, ideal for use in hospitality, education, retail, offices and more. Package contents- Device- Power cable- Brackets for 19" rackTechnical parametersConnectors and interfaces- LAN speed: (24) 100M/16/2.5G- Optical interfaces: (4) 10 Gbit/s- Serial port: Micro-USB, RJ45Power supply- via plug/terminal: 230 V ACPhysical properties- Design: Rackmount- Fan: (1) 40 x 40 mm- Housing design: Metal- Operating temperature [°C]: 0 to 45- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 180General- Switching capacity [Gbit/s]: 200- MAC address table: 32000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 148.8Software- Web management: Yes-Management: Web management, SSH, Telnet, Omada controller- Functions: VLAN, QoS, DHCP snooping- Default IP address: 192.168.0.1- Default login and password: admin / admin

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

