

Item no.: 374959

## ARCHER VR400 - Wireless VDSL/ADSL modem and router

from **68,59 EUR**

Item no.: 374959  
shipping weight: 0.90 kg  
Manufacturer: TP-LINK



### Product Description

The Archer VR400 unlocks the full potential of your internet connection by providing combined dual band Wi-Fi speeds of up to 1.2Gbps, including 300Mbps on the 2.4GHz band and 867Mbps on the 5GHz band, eliminating lag and buffering from your online experience. Two dedicated Wi-Fi networks support more devices and reduce wireless interference to create stable connections. The latest VDSL2 technology allows the Archer VR400 to deliver impressive VDSL broadband speeds of up to 100Mbps, which is almost five times faster than ADSL2+. The Archer VR400 serves as a DSL modem and wireless router, combining two devices in one. The integrated DSL port supports all standard DSL connections, including VDSL2, ADSL2+, ADSL2, and ADSL. With multiple inputs, the Archer VR400 provides you with a variety of options when connecting to the Internet. As a backup, the E-WAN port allows the Archer VR400 to accept connections from cable and fibre modems via Ethernet cable. Additionally, the USB port supports 3G/4G dongle connections.

**Specifications:**  
**Hardware:** Ethernet Ports: 3 10/100/1000Mbps RJ45 LAN Ports, 1 10/100/1000Mbps RJ45 WAN/LAN Port, 1 RJ11 Port- USB Port: 1 USB 2.0- Button: WPS Button, Wi-Fi On/Off Button, Reset Button- External Power Supply: 12V/1A- Dimensions (W x D x H): 8.5 x 4.9 x 1.2 in (215.6 x 124.6 x 31.6 mm)- IEEE Standards: IEEE 802.3, IEEE 802.3u, 802.3ab- VDSL2 Standards: ITU G.993.2, Up to 17a profile (POTS), ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP)- ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs),- ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis),- ADSL2+ Standards: ITU-T G.992.5- Antenna Type: 2 fixed Omni-Directional antennas  
**Wireless:** Wireless Standards: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz - Frequency: 2.4 GHz and 5 GHz- Signal Rate: 867Mbps at 5 GHz, 300Mbps at 2.4 GHz- Transmit Power: <20dBm (2.4 GHz), <23dBm (5 GHz)- Wireless Function: Enable/Disable Wireless Radio, WMM, Wireless Statistics- Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions- Wireless Schedule: Support 2.4 GHz and 5 GHz Wireless Schedule  
**Software:** Operation Modes: VDSL/ADSL Modem Router, Wireless Router, 3G/4G Router- DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP Relay- Port Forwarding: Virtual Server, Port Triggering, DMZ, ALG, UPnP- Dynamic DNS: DynDns, NO-IP, TP-Link- VPN: OpenVPN, PPTP VPN, IPSec VPN- ATM/PPP Protocols: ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER/IPvE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs- Security: NAT Firewall, SPI Firewall, Access Control, Service Filtering, Denial of Service (DoS), SYN Flooding, Ping of Death, IP and MAC Address Binding- Advanced Functions: Parental Controls, Network Address Translation(NAT), Port Mapping (Grouping), Static Routing, RIP v1/v2 (optional), DDNS, IGMP V1/V2/V3- Management: Web Based Configuration (HTTP / HTTPS ), Remote management, Command Line Interface, SSL for TR-069, SNMP v1/2c, Firmware Upgrade, Diagnostic Tools, Free Online Firmware Update- Guest Network: 2.4GHz Guest Network, 5GHz Guest Network- Protocols: Supports IPv4 and IPv6  
**Others:** Certification: CE, RCM, RoHS - System Requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, Mac OS, NetWare, UNIX or Linux, Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser  
**Subscription:** with an internet service provider (for internet access) - Environment Operating Temperature: 0°C~40°C (32°F ~104°F), Operating Humidity: 10%~90% non-condensing  
**Package contains:** Device- Power adapter 12V / 1.5A- RJ11 cable- RJ45 cable- External splitter

### Specifications

Scan this QR code to view the product  
All details, up-to-date prices and availability

