

Item no.: 392262

SG3452XP - TL- JetStream PoE switch

from **988,23 EUR**

Item no.: 392262
 shipping weight: 6.60 kg
 Manufacturer: TP-LINK



Product Description

The Jetstream TL-SG3452XP PoE switch from TP-Link is a manageable L2+ switch with PoE function that includes 48 Gigabit LAN ports with 802.3af/at PoE function and an additional 4x SFP+ ports with a speed of 1/10 Gbps. The switch has a total PoE budget of 500 W for the power supply of devices via a cable, the switch can be mounted in a 19" rack and cooling is provided via 3 ventilation openings on the side. Important features- 500 W PoE budget: 48x 802.3af/at-compliant PoE+ ports- 48x Gigabit PoE+ ports and 4x 1/10 Gbps SFP+ slot- Integration with Omada SDN: Zero-touch provisioning, centralised cloud management and intelligent monitoring- Centralised management: Cloud access and Omada app for easy management - Security: IP-MAC port binding, ACL, port security, DoS Defend, storm control, DHCP snooping, 802.1X, Radius Authentication, and much more- Optimisation of voice and video applications: L2/L3/L4 QoS and IGMP Snooping- Standalone management: Web, CLI (Console Port, Telnet, SSH), SNMP, RMON and Dual Image provide powerful management options Omada Controller The Omada Software Defined Networking (SDN) platform integrates network devices, including access points, switches, gateway routers and provides 100% centralised management in the cloud. Omada creates a highly scalable network including control from a single interface. Provides seamless wireless and wired connectivity, ideal for use in hospitality, education, retail, offices and more. Package contents- Device- Power cable- Brackets for 19" rack Technical parameters- Connectors and interfaces- LAN speed: (48) 10/100/1000 Mbit/s- Optical interfaces: (4) 1G/10Gbit/s- Serial connection: Micro-USB, RJ45 Power- Power type: Mains power (230 V)- PoE type: PoE-Out (only)- PoE-Out standards: 802.3af, 802.3at- PoE-Out ports: 48- PoE budget [W]: 500- Max. Power consumption [W]: 49- Power supply via plug/terminal: 230 V AC Physical properties- Design: Rackmount- Fan: (3) 40 x 40 mm- Housing design: Metal- Buttons: Status (speed / PoE)- Operating temperature [°C]: 0 to 40- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 330 General- Switching capacity [Gbit/s]: 176- MAC address table: 16000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 131 Software- Web management: Yes- Management: Web management, Omada controller, SSH, Telnet- Functions: VLAN, QoS, DHCP snooping- Default IP address: 192.168.0.1- Default login and password: admin / admin

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

