

Item no.: 392203

SG3210XHP-M2 - TL- JetStream PoE switch

from **467,36 EUR**

Item no.: 392203
shipping weight: 3.00 kg
Manufacturer: TP-LINK



Product Description

The TL-SG3210XHP-M2 is a network edge access switch that offers 10x 100/1000/2500 Mbps LAN ports with PoE function (802.3af/at) for powering VoIP/cameras and other devices, a PoE budget of 240 W and a maximum consumption of 30 W/port. In addition, 2x 10G SFP+ slots are available for further network expansions. For management and monitoring, it is possible to use general access via a web interface and protocols such as CLI, SNMP, RMO as well as centralised cloud management and a software controller. The Omada hardware controller (OC200 / OC300) is also supported. Key features- 2.5Gbps port speed - ports exceed the Gigabit limit - suitable for NAS / servers / WiFi6 etc.- PoE budget 240W- (10) 802.3af/at PoE- (2) 10Gbps SFP+ slots for easy network expansion- SW functions: IP-MAC port binding, ACL, Port Security, DoS Defend, Storm control, DHCP Snooping, 802.1X, Radius Authentication a mnoho ďalših- Centralised management: Cloud access and Omada app for maximum convenience and easy management- Standalone management: Web, CLI (Console Port, Telnet, SSH), SNMP, RMON and Dual Image provide powerful management capabilities- Static routing: Helps route internal traffic for more efficient use of network resources. Package contains- Device- Power cable- Rackmount ears Technical parameters Connectors and interfaces- LAN speed: (8) 100/1000/2500 Mbit/s- Optical interfaces: (2) 10 Gbit/s- Serial connection: Micro-USB, RJ45 Power supply- Power type: Mains power (230 V)- PoE type: PoE-Out (only)- PoE-Out standards: 802.3af, 802.3at- PoE-Out ports: 8- PoE budget [W]: 240- Max. Power consumption [W]: 17- Power supply via plug/terminal: 230 V AC Physical properties- Design: Rackmount- Fan: (2) 40 x 40 mm- Housing design: Metal- Operating temperature [°C]: 0 to 45- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 180 General- Switching capacity [Gbit/s]: 80- MAC address table: 16000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 59.5 Software- Web management: Yes- Management: Web management, Omada controller- Functions: VLAN, QoS, DHCP snooping- Default IP address: 192.168.0.1- Default login and password: admin / -

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

