

Item no.: 391307

MX-EX2028PXA-E - cnMatrix EX2028-P PoE switch

from **1.896,31 EUR**

Item no.: 391307
shipping weight: 4.80 kg
Manufacturer: Cambium Networks



Product Description

Cambium Networks cnMatrix EX2028-P is an L2/L3-manageable PoE switch with two fans on the side. The switch offers 24x Gigabit LAN with PoE-out 802.3af/at on all ports, maximum PoE consumption of 30 W/port, total PoE budget of 400 W, four SFP+ ports, Ethernet port for local management, serial console and USB port. The switch has a metal housing with a height of 1U and can be installed in a 19-inch rack. Cambium Networks' next-generation switch platform offers a cloud-based or web-based, powerful and feature-rich Ethernet switching solution. The cnMatrix switch platform offers:- Energy efficient Gigabit- Layer 3 (OSPF and RIP)- More port density options Connectors and interfaces- LAN speed: (24) 10/100/1000 Mbit/s- Management LAN: (1) 10/100 Mbit/s- Optical interfaces: (4) 10 Gbit/s- Serial connection: RJ45 Power- Power type: Mains power (230 V)- PoE type: PoE-Out (only)- PoE-Out standards: 802.3af, 802.3at- PoE-Out ports: 24- PoE budget [W]: 400- Max. Power consumption [W]: 25- Power supply via plug/terminal: 230 V AC Features- Design: Rackmount- Fan: (2) 40 x 40 mm- Housing design: Metal- Buttons: Reset- Operating temperature [°C]: 0 to 50- Width [mm]: 440- Height [mm]: 44- Depth [mm]: 250 General- Switching capacity [Gbit/s]: 128- MAC address table: 16000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 120 Software- Web management: Yes- Management: Web management, SSH, Telnet, Cambium cnMaestro Cloud- Functions: VLAN, QoS, DHCP snooping

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

