

Item no.: 392277

SX3206HPP - TL- JetStream PoE switch

from **620,91 EUR**

Item no.: 392277
shipping weight: 2.70 kg
Manufacturer: TP-LINK



Product Description

The Jetstream TL-SX3206HPP PoE switch from TP-Link is a manageable L2 switch with PoE function that includes 4x 10 Gigabit LAN ports with 802.3af/at/bt PoE with an upper limit of 60W/port and an additional 2x 10 Gigabit SFP+ ports that are also backward compatible with 1G modules. The switch has a total PoE budget of 200 W for powering devices via cable, and thanks to the wide range of accessories, the switch can also be conveniently mounted in a 19" rack using the rack ears included in the scope of delivery. Sufficient cooling is provided by 2 fans. Important features- PoE budget 200 W, 4x 802.3at/af/bt (60 W/port)- 4x 10-Gigabit PoE+ ports and 2x 10-Gigabit SFP+ slot- Integration with Omada SDN- Zero-touch provisioning, centralised cloud management and intelligent monitoring- Centralised management: Cloud access and Omada app for easy management- Static routing- Security: IP-MAC port binding, ACL, port security, DoS Defend, storm control, DHCP snooping, 802.1X, Radius Authentication, and much more- Optimisation of voice and video applications: L2/L3/L4 QoS and IGMP Snooping- IPv6 support including Dual IPv4/IPv6 Stack, MLD Snooping and IPv6 Neighbour Discovery/Packaging contents- Device- Power cable- Brackets for 19" rackConnections and interfaces- LAN speed: (4) 100M/1G/2.5G/5G/10Gbps- Optical interfaces: (2) 1G/10Gbps- Serial connection: micro USB, RJ45Power supply- Power type: Mains power (230V)- PoE type: PoE-Out (only)- PoE-Out standards: 802.3af, 802.3at, 802.3bt- PoE outputs: 4- PoE budget [W]: 200- Max. Power consumption [W]: 27- Power supply via plug/terminal: 230V ACPhysical properties- Design: Desktop, rackmount- Fan: (2) 40 x 40 mm- Housing design: Metal- Buttons: Reset- Operating temperature [°C]: 0 to 50- Width [mm]: 294- Height [mm]: 44- Depth [mm]: 180General- Distribution capacity [Gbps]: 120- MAC address table: 32000- Jumbo frame [bytes]: 9000- Packet forwarding rate [Mpps]: 89.3Software- Web management: Yes- Management: Web management, SSH, Telnet, Omada controller- Functions: VLAN, QoS, DHCP snooping- Default IP address: 192.168.0.1- Default login and password: admin / admin

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

