

Item no.: 391332

## PL-E700X00A-RW - cnPilot e700 - without PoE injector, RoW

from **1.174,15 EUR**

Item no.: 391332  
 shipping weight: 2.50 kg  
 Manufacturer: Cambium Networks



### Product Description

Outdoor 4x4:4 MU-MIMO dual band 2.4 GHz and 5 GHz 802.11ac wave2 Access Point with PoE injector, 512 users, 16 SSIDs, 400 Mbps data rate on 2.4 GHz, 1733 Mbps data rate on 5 GHz, dual Gigabit Ethernet port (2 x 10/100/1000Base-T), integrated 8 dBi omnidirectional antenna, PoE powered, integrated electrical heater for cold start, ruggedized - ESD protection, special LTE resilience filtering, UV rated IP67 enclosure, max operating temperature range -40°C ~ +65°C, operating humidity 10% to 95%, packaged with wall mount brackets. Package contains- Device- Holder- (2) metal strap- (2) cable gland- Screws Wireless features- Wireless frequency: 2.4 + 5 GHz (dual band)- WiFi standards: 802.11ac, 802.11ac - wave2, 802.11n, 802.11a, 802.11b/g- MU-MIMO: Yes- Hotspot 2.0: Yes- Transmission speed - 5GHz [Mb/s]: 1733- Transmission speed - 2.4GHz [Mb/s]: 400- Tx power 2.4GHz [dBm]: 25- Tx power 5GHz [dBm]: 28- Security: WPA-PSK/WPA2-PSK- 2.4GHz MIMO: 2 x 2- 5GHz MIMO: 4 x 4- Type of antenna: Built-in- Internal antennas: 6- Roaming: Yes- Antenna gain [dBi]: 8 Connectors and Interfaces- LAN speed: (2) 10/100/1000Mbps- Gigabit LAN: Yes Power- Power over Ethernet: 802.3at- Power type: PoE- PoE type: PoE-Out + PoE-In- Max. power consumption [W]: 25 Physical characteristics- Protection class: IP67- Purpose: Outdoor- Operating temperature [°C]: -40 up to 65- Weight [g]: 1700- Width [mm]: 215- Height [mm]: 315- Depth [mm]: 66 Software- Operating mode: Access Point- IPv6 support: Yes- Default IP address: 192.168.0.1, Dynamic from DHCP- Default login and password: admin / admin

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

