

Item no.: 395761

PR3PUUS3 - US power supply, 9W

from **8,01 EUR**

Item no.: 395761
shipping weight: 0.10 kg
Manufacturer: Teltonika



Product Description

US POWER SUPPLY, 9W
TECHNICAL DATA
GENERAL
Input voltage- 100 – 240 VAC
Input frequency- 50 / 60 Hz
Input current- 0.4 A
Input connector- US (Type A)
Output voltage- 9 VDC
Output current- 1.0 A
Output connector- 4-pin, 3 mm pitch
ADDITIONAL
Input voltage range- 90 – 264 VAC
Input frequency range- 47 – 63 Hz
Maximum input inrush current- 40 A
Output voltage maximum deviation- 8.55 – 9.45 VDC
Short circuit protection- Yes
HIPOT (dielectric withstand test)- Primary to Secondary: 3000 VAC
MTBF- 50000 h
Certification- UL 60950-1- CSA C22.2 No. 60950-1-07- 47 CFR FCC part 15 subpart B, 10-1-2016- ANSI C63.4:2014- IEC 62321-7-1:2015, IEC 62321-6:2015, IEC 62321-5:2013, IEC 62321-4:2013, IEC 62321:2008 Annex C

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

