

Item no.: 395749

PR320AUA - AU 2-pin power supply, 250W

from **95,66 EUR**

Item no.: 395749
shipping weight: 0.20 kg
Manufacturer: Teltonika



Product Description

AU 2-PIN POWER SUPPLY, 250W
TECHNICAL DATA
GENERAL
Input voltage- 100 – 240 VAC
Input frequency- 50 / 60 Hz
Input current- 3.9 A
Input connector- AU (Type I)
Output voltage- 54 VDC
Output current- 4.62 A
Output connector- 2-pin, with cord end terminals
Weight- 910 g
ADDITIONAL
Input voltage range- 90 – 264 VAC
Input frequency range- 47 – 63 Hz
Maximum input inrush current- 60 A
Output voltage maximum deviation- 51.3 – 56.7 VDC
Short circuit protection- Yes
HIPOT (dielectric withstand test)- Primary to Secondary: 1500 VAC
Certification- Safety: IEC62368-1 (CB Scheme)- EMC: AS/NZS CISPR 32:2015, EN 55032:2015, EN IEC 61000-3-2:2019, EN 61000-3-3:2013, EN 61000-4-2:2009, EN 61000-4-3:2006+A1:2008+A2:2010, EN 61000-4-4:2012, EN 61000-4-5:2014, EN 61000-4-6:2014, EN 61000-4-8:2010, EN 61000-4-11:2004

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

