

Item no.: 395765

PR3PXAU3 - AU power supply, 18W

from **10,11 EUR**

Item no.: 395765
shipping weight: 0.10 kg
Manufacturer: Teltonika



Product Description

AU POWER SUPPLY, 18W
TECHNICAL DATA
GENERAL
Input voltage- 100 – 240 VAC
Input frequency- 50 / 60 Hz
Input current- 0.6 A
Input connector- AU (Type I)
Output voltage- 12 VDC
Output current- 1.5 A
Output connector- 4-pin, 3 mm pitch
Weight- 89 g
ADDITIONAL
Input voltage range- 90 – 264 VAC
Input frequency range- 47 – 63 Hz
Maximum input inrush current- 60 A
Output voltage maximum deviation- 11.4 – 12.6 VDC
Short circuit protection- Yes
HIPOT (dielectric withstand test)- Primary to Secondary: 4000 VDC
MTBF- 30000 h
PSU efficiency standard- DoE Level VI
Certification- Safety: AS/NZS 62368.1:2018, AS/NZS 3112:2017 - EMC: AS/NZS CISPR 32:2015, EN 55032:2015, EN 55035:2017, EN 61000-3-2:2019, EN 61000-3-3:2013+A1:2019

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

