

Item no.: 395759

PR3PUAU3 - AU power supply, 9W

from **7,31 EUR**

Item no.: 395759
shipping weight: 0.10 kg
Manufacturer: Teltonika



Product Description

TECHNICAL DATA
GENERAL Input voltage- 100 – 240 VAC Input frequency- 50 / 60 Hz Input current- 0.45 A Input connector- AU (Type I) Output voltage- 9 VDC Output current- 1.0 A Output connector- 4-pin, 3 mm pitch Weight- 80 g
ADDITIONAL Input voltage range- 90 – 264 VAC Input frequency range- 47 – 63 Hz Maximum input inrush current- 60 A Output voltage maximum deviation- 8.55 – 9.45 VDC Short circuit protection- Yes HIPOT (dielectric withstand test)- Primary to Secondary: 4000 VDC MTBF- 30000 h PSU efficiency standard- DoE Level VI Certification- Safety: AS/NZS 62368-1: 2018, AS/NZS 3112: 2017, IEC 62368-1:2014/A11:2017 (CB Scheme)- EMC: EN 55032:2015, EN 55035:2017, IEC 61000-4-2:2008, IEC 61000-4-3:2006+A1:2007+A2:2010, IEC 61000-4-4:2012, IEC 61000-4-5:2014, IEC 61000-4-6:2013, IEC 61000-4-11:2004, EN 61347-1:2015, EN 61347-2-13:2014/A1:2017, EN 62493:2015

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

