

Item no.: 395759

PR3PUAU3 - AU power supply unit, 9W

from **7,60 EUR**

Item no.: 395759
shipping weight: 0.10 kg
Manufacturer: Teltonika



Product Description

TECHNICAL DATAGENERAL- Input voltage: 100 - 240 VAC- Input frequency: 50 / 60 Hz - Input current: 0.45 A- Input connector: AU (type I)- Output voltage: 9 VDC- Output current: 1.0 A- Output connector: 4-pin, 3 mm pitch- Weight: 80 gADDITIONAL PARTS- Input voltage range: 90 - 264 VAC- Input frequency range: 47 - 63 Hz- Maximum input inrush current: 60 A- Maximum output voltage deviation: 8.55 - 9.45 VDC- Short circuit protection: Yes- HIPOT (dielectric resistance test): Primary to Secondary: 4000 VDC- MTBF: 30000 h- PSU Efficiency Standard: DoE Level VI- Certification: Safety: AS/NZS 62368-1: 2018, AS/NZS 3112: 2017, IEC 62368-1:2014/A11:2017 (CB Scheme), EMC: EN 55032:2015, EN -55035:2017, IEC 61000-4-2:2008, IEC 61000-4-3:2006+A1:2007+A2:2010, IEC 61000-4-4:2012, IEC 61000-4-5:2014, IEC 61000-4-6:2013, IEC 61000-4-11:2004, EN 61347-1:2015, EN 61347-2-13:2014/A1:2017, EN 62493:2015

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

