

Item no.: 395753

## PR3P2AU3 - AU power supply unit, 24 W

from **11,97 EUR**

Item no.: 395753  
shipping weight: 0.10 kg  
Manufacturer: Teltonika



### Product Description

AU POWER SUPPLY, 24 W Technical data- Input voltage: 100 - 240 VAC- Input frequency: 50 / 60 Hz- Input current: 0.8 A- Input connector: AU (type I)- Output voltage: 12 VDC- Output current: 2.0 A- Output connector: 4-pin, 3 mm pitch-Weight: 115 g Additionally- Input voltage range: 90 - 264 VAC- Input frequency range: 47 - 63 Hz- Maximum input inrush current: 60 A- Maximum output voltage deviation: 11.4 - 12.6 VDC- Short-circuit protection: Yes- HIPOT (dielectric resistance test): Primary to Secondary: 4000 VDC- MTBF: 30000 h- PSU Efficiency Standard: DoE Level VI- Certification Safety: AS/NZS 60950.1:2015, AS/NZS 60065:2012 Inc A1 EMC: AS/NZS CISPR 22:2009+A1:2010, AS/NZS CISPR 13:2012, EN 55032:2012, EN 55024:2010, EN 55020:2007+A11, EN 61000-3-2:2014, EN 61000-3-3:2013

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

