

Item no.: 395753

## PR3P2AU3 - AU power supply, 24W

from **11,51 EUR**

Item no.: 395753  
shipping weight: 0.10 kg  
Manufacturer: Teltonika



### Product Description

AU POWER SUPPLY, 24W  
TECHNICAL DATA  
GENERAL  
Input voltage- 100 – 240 VAC  
Input frequency- 50 / 60 Hz  
Input current- 0.8 A  
Input connector- AU (Type I)  
Output voltage- 12 VDC  
Output current- 2.0 A  
Output connector- 4-pin, 3 mm pitch  
Weight- 115 g  
ADDITIONAL  
Input voltage range- 90 – 264 VAC  
Input frequency range- 47 – 63 Hz  
Maximum input inrush current- 60 A  
Output voltage maximum deviation- 11.4 – 12.6 VDC  
Short circuit protection- Yes  
HIPOT (dielectric withstand test)- Primary to Secondary: 4000 VDC  
MTBF- 30000 h  
PSU efficiency standard- DoE Level VI  
Certification- Safety: AS/NZS 60950.1:2015, AS/NZS 60065:2012 Inc A1- EMC: AS/NZS CISPR 22:2009+A1:2010, AS/NZS CISPR 13:2012, EN 55032:2012, EN 55024:2010, EN 55020:2007+A11, EN 61000-3-2:2014, EN 61000-3-3:2013

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

