

Item no.: 395754

PR3P2UK3 - UK power supply, 24W

from **11,59 EUR**

Item no.: 395754
shipping weight: 0.20 kg
Manufacturer: Teltonika



Product Description

UK POWER SUPPLY, 24W
TECHNICAL DATA
GENERAL
Input voltage- 100 – 240 VAC
Input frequency- 50 / 60 Hz
Input current- 0.8 A
Input connector- UK (Type G)
Output voltage- 12 VDC
Output current- 2.0 A
Output connector- 4-pin, 3 mm pitch
Weight- 120 g
ADDITIONAL
Input voltage range- 90 – 264 VAC
Input frequency range- 47 – 63 Hz
Maximum input inrush current- 60 A
Output voltage maximum deviation- 11.4 – 12.6 VDC
Short circuit protection- Yes
HIPOT (dielectric withstand test)- Primary to Secondary: 4000 VDC
MTBF- 30000 h
PSU efficiency standard- DoE Level VI
Certification- Safety: EN 62368-1:2014+A11:2017- EMC: EN 55032:2015, Class B; EN 55024:2010; EN 61000-3-2:2014; EN 61000-3-3:2013- Energy efficiency: EN 50563:2011+A1:2013; EN 50564:2011; 10 CFR 430 Appendix Z: 2015

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

