

Item no.: 391382

RG-RAP2200(E) - Reyee access point

from **72,38 EUR**

Item no.: 391382
 shipping weight: 0.70 kg
 Manufacturer: Cambium Networks



Product Description

RG-RAP2200(E) is a wireless Wi-Fi 5 access point / AP router from Ruijie Networks with ceiling or wall mount and full roaming support for seamless transition between APs. The device is equipped with two Gigabit LAN ports, the first of which supports power over 802.3at PoE, Dual Band Wi-Fi 5 2x2 MU-MIMO radio with modulation rates of 400 Mbps in the 2.4 GHz and 867 Mbps in the 5 GHz band. Key benefits- Easily expandable Wi-Fi with Reyee Mesh- (2) 10/100/1000 Mbps LAN- Support for MU-MIMO, roaming, OFDMA- High throughput thanks to Wi-Fi 5 and 2x2 MIMO in both bandsInterior- Power supply via 802.3at PoE and 12V DC connection- Management via Ruijie Reyee Cloud or web interfaceTechnical parametersWireless features- Wireless frequency: 2.4 + 5 GHz (dual band)- WiFi standards:802.11ac802.11ac - wave2802.11n802.11a802.11b/g- MU-MIMO: Yes- Transmission speed - 5GHz [Mb/s]: 866- Transmission speed - 2.4GHz [Mb/s]: 400- Transmission power 2.4GHz [dBm]: 20- Transmission power 5GHz [dBm]: 20- Security: WPA-PSK/WPA2-PSK- 2.4GHz MIMO: 2 x 2- 5GHz MIMO: 2 x 2- Antenna type: Built-in- Internal antennas: 2- Roaming: Yes- Antenna gain [dBi]: 2Connections and interfaces- LAN speed: (2) 10/100/1000Mbps- Gigabit LAN: YesPower supply- Power over Ethernet: 802.3at- PoE type: PoE-In (only)- Max. Power consumption [W]: 13- Power supply via plug/terminal: 12V / 1.5APhysical properties- Purpose: Indoor- Buttons: Reset- Operating temperature [°C]: 0 to 40- Weight [g]: 450- Width [mm]: 194- Height [mm]: 35- Depth [mm]: 194Software- Operating mode:AP RouterAccess Point- Default IP address: Dynamic from DHCP, 10.44.77.253- Default login and password: Set by the user when switching on for the first time

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

