

Item no.: SC-2409-0611-2750

UVC-G4 DOORBELL PRO-EU - G4 Doorbell Pro, WiFi-connected video doorbell, 5MP nightvision

296,25 EUR

Item no.: SC-2409-0611-2750
shipping weight: 0.40 kg
Manufacturer: Ubiquiti



Product Description

G4 Doorbell Pro, WiFi-connected video doorbell, 5 MP nightvision

The G4 Doorbell Pro is a WiFi-enabled video doorbell equipped with a primary 5 MP camera and a secondary 8 MP package camera. The doorbell's main camera is equipped with IR LED to provide enhanced night vision that, when combined with the built-in porch light, ensures a reliably clear surveillance feed around the clock. The G4 Doorbell Pro also features echo-cancelling, two-way audio so you can interact with visitors, and its programmable display allows you to give alerts or delivery instructions to couriers. Designed to be a powerful, plug-and-play security tool, the G4 Doorbell Pro can be set up and configured in minutes with the UniFi Protect application.

Mechanical

- Dimensions: 160.6 x 51.7 x 28.7 mm (6.32 x 2.03 x 1.13")
- Weight: Without mount: 253 g (8.92 oz); With flat wall mount: 286 g (10.08 oz); With 20° wedge mount: 325 g (11.46 oz)
- Enclosure materials: Polycarbonate, aluminum alloy
- Mounting materials: Flat wall mount: aluminum alloy; 20° wedge mount: polycarbonate
- Weatherproofing: IPX4

Optics

- Sensor: 5 MP CMOS sensor
- Lens: Fixed focal length
- View angle: H: 138°, V: 114°, D: 155°
- Night mode: IR LED illumination and an IR cut filter

Video

- Video compression: H.264
- Resolution: 1600 x 1200 (4:3)
- Maximum frame rate: 30 FPS

System

- Processor specs: Quad core Arm® Cortex®-A53 based chip
- Memory information: 512 MB
- Management interface: UniFi Protect application
- Networking interface: 802.11a/b/g/n/ac WiFi; Bluetooth™ 5.0; GbE support (with UACC-Adapter-DBPOE)
- Flash memory support: 256 MB
- Max. power consumption: 10 VA
- Power requirements: 16 to 24 V AC, 1.25 A max., 50/60 Hz; USB-C power cable, 5 V DC, 2 A
- Supported voltage range: 37 to 57 V DC
- Link/activity LED: Yes
- Button: Factory reset
- Mounting: Flat wall, 20° wedge (kits included)
- Operating temperature: -10°C to 40°C (14°F to 104°F)
- Operating humidity: 10 to 90% noncondensing
- Certifications: FCC, IC, CE

Audio

- Microphone: Yes (can be disabled)
- Speaker: Yes

Software

- UniFi OS application: UniFi Protect
- Mobile app: UniFi Protect (iOS and Android)

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

