

Item no.: 392190

## SG2210MP - JetStream Smart PoE Switch

from **181,06 EUR**

Item no.: 392190  
 shipping weight: 2.30 kg  
 Manufacturer: TP-LINK



### Product Description

The Jetstream TL-SG2210MP PoE switch from TP-Link is a manageable L2 switch with PoE functionality that includes 8 Gigabit LAN ports with 802.3af/at PoE support and an additional 2 Gigabit SFP ports. The switch has a PoE budget totalling 150W for the power supply of all devices (access points, VoIP, IP cameras,...) via cable. The switch can be installed in a 19" rack and 1 fan on the side provides cooling. Features- 150 W PoE budget: 8x 802.3af/at-compliant PoE+ ports with a total power supply of 150 W- Full Gigabit ports: 8x Gigabit PoE+ ports and 2x Gigabit SFP slots provide high-speed connections.- Integrated with Omada SDN: Zero-touch provisioning (ZTP)\*\* , centralised cloud management and intelligent monitoring.- Centralised management: Cloud access and Omada app for maximum convenience and easy management.- Static routing: Helps route internal traffic for more efficient use of network resources.- Robust security strategies: IP-MAC Port Binding, ACL, Port Security, DoS Defend, Storm Control, DHCP Snooping, 802.1X, Radius Authentication and more.- Voice and Video Application Optimisation: L2/L3/L4 QoS and IGMP Snooping.- IPv6: IPv6 support with dual IPv4/IPv6 stack, MLD snooping, IPv6 neighbour discovery. Package contains- Device- Power cable- 19" rackmount ears Technical parameters- Connectors and Interfaces LAN speed: (8) 10/100/1000Mbps Optical interfaces: (2) 1000Mbps- Power Power type: Mains power (230V) PoE type: PoE-Out (only) PoE-Out standards: 802.3af, 802.3at PoE Out ports: 8 PoE budget [W]: 150 Max. power consumption [W]: 12.2 Power via connector/terminal: 230V AC- Physical characteristics Design: Desktop, Rackmount Fans: (1) 40 x 40 mm Chassis design: Metal Buttons: Reset Operating temperature [°C]: 0 up to 50 Width [mm]: 294 Height [mm]: 44 Depth [mm]: 180- General Switching capacity [Gbps]: 20 MAC address table: 8000 Jumbo frame [Bytes]: 9000 Packet forwarding rate [Mpps]: 14.9- Software Web management: Yes Management: Web management, SSH, Telnet, Omada controller Features: VLAN, QoS, DHCP snooping Default IP address: 192.168.0.1 Default login and password: admin / admin

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

