

Item no.: 390872

## EFG Enterprise-grade 25 Gbps UniFi Cloud Gateway with three WAN ports, high availability

from **1.441,86 EUR**

Item no.: 390872  
 shipping weight: 7.00 kg  
 Manufacturer: Ubiquiti



### Product Description

25G Cloud Gateway with 500+ UniFi device / 5,000+ client support, 12.5 Gbps IPS routing, and complete high availability.- Runs UniFi Network for full-stack network management- Shadow Mode High Availability with automatic failover provides uninterrupted connectivity (VRRP)\*- 12.5 Gbps routing with IDS/IPS- License-free, real-time inspection of encrypted packets with NeXT AI Inspection (SSL/TLS decryption)- (2) 25G SFP28\*\*, (2) 10G SFP+\*\*, and (2) 2.5 GbE RJ45 ports (two interfaces remappable to WAN)- (2) included hot-swap PSUs for power redundancy- 1.3" touchscreenMechanicalDimensions 442.4 x 43.7 x 325 mm (17.4 x 1.7 x 12.8")Weight 6.5 kg (14.3 lb)Enclosure material Aluminium CNC, SGCC steelHardware- Processor 18-core ARM® v8.2 at 2 GHz- System memory 16 GB DDR4 DIMM- Management interface - Ethernet Bluetooth- Networking interface(2) 25G SFP28 ports(2) 10G SFP+ ports(2) 2.5 GbE RJ45 portsMap any (2) interfaces to WAN- Power method (1) Universal AC input, 100–240V AC, 7A Max., 50/60 Hz- Power supply (2) Hot-swappable 150W CRPS- Supported voltage range 100–240V AC- Max. power consumption 82W- ESD/EMP protection Air: ± 8kV, contact: ± 4kV- LCM display (1) 1.3" touchscreen- Button Factory reset- Ambient operating temperature 0 to 40° C (22 to 104° F)- Ambient operating humidity 5 to 95% noncondensing- Certifications CE, FCC, ICGateway Features- PerformanceRedundant WAN with failover and load balancingWiFi QoS with UniFi APsApplication, domain, and country-based QoSApplication and device type identificationAdditional internet failover with LTE BackupInternet quality and outage reporting- Next-generation securityApplication-aware firewall rulesSignature-based IPS/IDS threat detectionContent, country, domain, and ad filteringVLAN/subnet-based traffic segmentationFull stateful firewall- Advanced networkingLicense-free SD-WANWireGuard, L2TP and OpenVPN serverOpenVPN clientOpenVPN and IPsec site-to-site VPNOne-click Teleport and Identity VPNPolicy-based WAN and VPN routingDHCP relayCustomizable DHCP serverIGMP proxyIPv6 ISP supportCapacity- UniFi devices 500+- Client devices 5,000+- Concurrent sessions 1 million- New sessions / sec 71,000- SSL/TLS inspection concurrent sessions 10,000Limiting to 5,000 concurrent sessions is recommended if the gateway is passing significant traffic. This can be achieved by restricting which VLANs and domains pass through NeXT AI Inspection, such as only including search engine and LLM queries on employee devices. Learn more.- IDS/IPS signatures 80,000+With Enhanced Threat Updates. Learn more.Routing Throughput- Firewall 23.5 Gbps- IDS/IPS 12.5 GbpsMeasured with iPerf3 on DHCP WAN. Performance may be reduced with PPPoE depending on ISP implementation.VPN Server Single User Throughput- UniFi Identity 1.2 Gbps- Teleport 1.2 Gbps- WireGuard 1.2 Gbps- OpenVPN 210 Mbps- L2TP 280 MbpsMeasured with iPerf3.Site-to-Site VPN Single Tunnel Throughput- Site Magic 1.1 Gbps- OpenVPN 120 Mbps- IPsec 580 MbpsMeasured with iPerf3.VPN Client Single Tunnel Throughput- WireGuard 980 Mbps- OpenVPN 180 MbpsMeasured with iPerf3.LEDs- Ethernet White: Link/activity- SFP+ White: Link/activity- CRPSOff: No AC power presentSteady white: AC power and DC output activeFlashing white: AC power presentSteady red: AC power lost/failure eventsFlashing red: Warning eventsSoftware- Mobile appUniFi iOS™:Version 10.16.2 and laterUniFi Android™: Version 10.17.2 and later

### Specifications

Scan this QR code to view the product  
 All details, up-to-date prices and availability

