

Item no.: 391419

## RG-RAP6260(H) - Reyee access point



from **257,17 EUR**

Item no.: 391419  
shipping weight: 5.60 kg  
Manufacturer: Ruijie Networks

### Product Description

Product description RG-RAP6260(H) is Ruijie Networks ceiling-mounted and wall-mounted wireless Wi-Fi 6 Access Point with full roaming support for seamless transition between APs. The device is equipped with a 2.5-Gigabit Ethernet port with support for power supply via 802.3bt PoE, a Gigabit SFP port for optical connection up to a distance of 20 km and Dual Band Wi-Fi 6 4x4 MU-MIMO radio with modulation speeds 1148 Mbps in 2.4 GHz and 4804 Mbps in the 5 GHz band using a 160 MHz wide channel. Main advantages- Easily expandable Wi-Fi with Reyee Mesh- 2.5-Gigabit Ethernet- SFP interface- Support MU-MIMO, Roaming, Beamforming, OFDMA and other technologies- High throughput thanks to WiFi 6 and 4x4 MIMO in both bands- Outdoor design, IP68 protection- Power supply via 48V DC connector or 802.3bt PoE- Management through Ruijie Reyee Cloud or web interface Package contents- Device- Holder and mounting plate- Screws- Cable grommets- (2) Tightening metal strap Product is for EU region only Technical parameters Wireless features- Wireless frequency: 2.4 + 5 GHz (dual band) - WiFi standards: 802.11ax, 802.11ac, 802.11ac - wave2, 802.11n, 802.11a, 802.11b/g - MU-MIMO: Yes - Transmission speed - 5GHz [Mb/s]: 4804 - Transmission speed - 2.4GHz [Mb/s]: 1148 - Tx power 2.4GHz [dBm]: 32 - Tx power 5GHz [dBm]: 32 - Security: WPA-PSK/WPA2-PSK - 2.4GHz MIMO: 4 x 4 - 5GHz MIMO: 4 x 4 - Type of antenna: Built-in - Internal antennas: 8 - Roaming: Yes - Antenna gain [dBi]: 3, 4 Connectors and Interfaces- LAN speed: (1) 100/1000/2500Mbps - Gigabit LAN: Yes - Optical interfaces: (1) 1000Mbps Power- Power over Ethernet: 802.3bt - PoE type: PoE-In (only) - Max. power consumption [W]: 40 - Power via connector/terminal: 48V / 1A Physical characteristics- Protection class: IP68 - Purpose: Outdoor- Button: Reset - Operating temperature [°C]: -30 up to 65 - Weight [g]: 3500 - Width [mm]: 300 - Height [mm]: 76 -Depth [mm]: 300 Software- Operating mode: Access Point - Default IP address: Dynamic from DHCP, 10.44.77.253 - Default login and password: Is set by the user at the first startup

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

