

Item no.: 398046

USW-FLEX-2.5G-5-EU -

from **56,04 EUR**

Item no.: 398046
shipping weight: 0.30 kg
Manufacturer: Ubiquiti



Product Description

Compact 2.5G switch with 5 ports that can be supplied with power via PoE or a USB-C adapter.- (4) 2.5GbE ports- (1) 2.5GbE PoE input port for power supply- Optional power supply with the supplied 5V, 1A USB-C adapterMechanical:- Dimensions: 117.1 x 90 x 21.2 mm (4.6 x 3.5 x 0.8")- Weight: 206 g (7.3 oz)- Housing material: polycarbonateHardware:- Management interface: Ethernet in-band- Network interface: (5) 1/2.5 GbE RJ45 ports- Total non-blocking throughput: 12.5 Gbps- Switching capacity: 25 Gbps- Forwarding rate: 18.6 Mpps- Power supply: (1) AC power supply, 5V DC, 1A; (1) PoE (PairA 1, 2+; 3, 6-)(PairB 4, 5+; 7, 8-)- External power supply: AC/DC adapter- UniFi PoE: Switch- Supported voltage range: AC/DC input: 5V DC- PoE input: 44-57V DC- Max. Power consumption AC/DC input: 5W- PoE input: 6.4 W- Button: Factory reset- Operating ambient temperature: -20 to 45° C (-4 to 113° F)- Operating humidity: 10 to 90% non-condensing- Certifications: CE, FCC, ICSwitching functions- Layer 2 functions: STP / RSTP with prioritisation and deactivation at port level; port isolation; storm control; port mirroring; multicast/broadcast rate limiting; flow control; jumbo frames; egress rate limiting- Layer 3 functions: -LEDs:- System: (1) Blue/White: Power; White flashing: Boot process in progress; Blue flashing: Firmware upgrade; White steady light: Factory settings; Device waiting for acceptance; Blue steady light: Device is accepted- Ethernet: (5) Green: Connection/activityApplication requirements:- UniFi Network Version 8.4.62 and higher

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

