

Item no.: 392200

## SG3428XF - JetStream switch

from **620,91 EUR**

Item no.: 392200  
 shipping weight: 4.30 kg  
 Manufacturer: TP-LINK



### Product Description

Jetstream Switch TL-SG3428XF from TP-Link is a manageable optical L3 switch equipped with optical 20x SFP + 4x SFP/GLAN combo and 4x SFP+ ports and two console ports (RJ45 and micro USB). The switch has a total switching capacity of 128 Gbit/s, 2 redundant sources with an input voltage of 230 V, a single fan, maximum consumption of 36 h and can be mounted in a 19" rack thanks to the ears supplied. Key features-24x SFP (4x Combo SFP/GLAN) + 4x SFP+-Omada SDN integration: Zero-touch provisioning, centralised cloud management and intelligent monitoring-Centralised management: Cloud access and Omada app for easy management-Static routing-Security: IP-MAC port binding, ACL, Port Security, DoS Defend, Storm control, DHCP -Snooping, 802.1X, Radius Authentication, and much more-Optimisation of voice and video applications: L2/L3/L4 QoS and IGMP Snooping-IPv6 support including Dual IPv4/IPv6 Stack, MLD Snooping and IPv6 Neighbour Discovery Omada Controller The Omada Software Defined Networking (SDN) platform integrates network devices, including access points, switches and gateway routers, and provides 100% centralised management in the cloud. Omada creates a highly scalable network including control from a single interface. Provides seamless wireless and wired connectivity, ideal for use in hospitality, education, retail, offices and more. Package contents-device-power cable-brackets for 19" rack Technical parameters Connectors and Interfaces LAN speed: (4) 10/100/1000Mbps Optical interfaces: (20) 1000Mbps + (4) 1000Mbps Combo + (4) 10Gbps Serial port: micro USB, RJ45 Power Power type: Mains power (230V) Redundant power supply: Yes Max. power consumption [W]: 36 Power via connector/terminal: 230V AC Physical characteristics Design: Rackmount Fans: (1) 40 x 40 mm Chassis design: Metal Operating temperature [°C]: 0 up to 45 Width [mm]: 440 Height [mm]: 44 Depth [mm]: 220 General Switching capacity [Gbps]: 128 MAC address table: 16000 Jumbo frame [Bytes]: 9000 Packet forwarding rate [Mpps]: 95.2 Software Web management: Yes Management: Web management, SSH, Telnet, Omada controller Features: VLAN, QoS, DHCP snooping Default IP address: 192.168.0.1 Default login and password: admin / admin

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

