

Item no.: 392279

SG3452XMPP - Omada managed switch L2+, PoE++, 750W

from **1.142,28 EUR**

Item no.: 392279
shipping weight: 7.10 kg
Manufacturer: TP-LINK



Product Description

This first-class PoE switch is ready for you with a budget of up to 750 W, PoE++ support and 4 optical SFP+ slots. Manage your access points, switches and gateways at multiple locations remotely via a single interface. Main features- 4x 10 Gbps SFP+ slots- 8x Gigabit 802.3af/at PoE++ ports (Max 90 W PoE budget for each port)- 40x Gigabit 802.3af/at PoE+ ports (Max. 30 W budget for each port)- Up to 750 W total PoE budget- Centralised cloud management via web or Omada app- Standalone management via web, CLI, SNMP and RMON- Static routing helps to route internal traffic for higher efficiency- VLAN, ACL, QoS, IGMP Snooping, OAM and DDM- ERPS supports fast protection and recovery in a ring topology- Robust metal housing and rack-mountable design Packaging contents- Device- Power cable- Quick installation guide- Rackmount kit- Rubber feet Technical parameters Connections and interfaces LAN speed: (48) 10/100/1000Mbps Optical interfaces: (4) 1G/10Gbps Serial port: micro USB, RJ45 Power supply Power type: Mains power (230V) PoE type: PoE-Out (only) PoE-Out standards: 802.3bt, 802.3af, 802.3at, 802.3at - ultra PoE (60W) PoE-Out ports: 48 PoE budget [W]: 750 Max. Power consumption [W]: 91.3 Power supply via plug/terminal: 230V AC Physical properties Design: Rackmount Fan: (3) 40 x 40 mm Housing design: Metal Buttons: Reset Operating temperature [°C]: 0 to 40 Width [mm]: 440 Height [mm]: 44 Depth [mm]: 330 General Distribution capacity [Gbps]: 176 MAC address table: 16000 Jumbo frame [bytes]: 9000 Packet forwarding rate [Mpps]: 130 Software Web management: Yes Management: Web management, Omada controller Functions: VLAN, QoS, L2+

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

