

Item no.: 391317

## B-C600500A004A - cnWave V5000 AP, 60GHz - Bazar

from **1.407,42 EUR**

Item no.: 391317  
shipping weight: 4.00 kg  
Manufacturer: Cambium Networks



### Product Description

Cambium Networks' 60 GHz cnWave solution provides simple, fast and cost-effective gigabit wireless connectivity for edge access and/or backhaul solutions with high capacity for edge access solutions at a significantly lower total cost of ownership than fibre infrastructure. Service providers and enterprises now have access to gigabit for business and residential connections, backhaul for Wi-Fi access or LTE/5G small cell. The Facebook Terragraph certified cnWave Mesh solutions are highly efficient in handling high-density deployments in cities and suburbs. Details V5000 is a 60GHz access point with two sector antennas with a 2x 140° beam angle (20° in vertical direction), an antenna gain of 22.5dBi and the ability to connect 4 distribution nodes or up to 30 CPE units. The device has a total of 2 Ethernet ports and an optical SFP+ slot. The first port supports 100M/1G and 10G speeds, including passive PoE IN 44-57V DC, and the second Gigabit port also supports PoE Out with the 802.3at standard, which is particularly suitable for powering cameras. The wireless part supports two bandwidths 2160MHz and 4320MHz (future firmware), the actual link speed is 7.6Gbps (3.8Gbps downlink, 3.8Gbps uplink) and supports PtMP, Mesh or PTP wireless modes. The maximum power consumption of the device is 35 W, when using PoE Out it can be up to 60 W.- The device can be managed via the web interface or the cnMaestro™ Cloud - Element Management System for easy deployment, monitoring and upgrades- Network planning with LINKPlanner Technical parameters Wireless functions- Channel bandwidth [MHz]: 2160, 4320- Transmission speed - 60GHz [Mb/s]: 7600, full duplex- Output power 60GHz [dBm]: 38 (EIRP)- Elevation beamwidth (-6dB) [°]: 20- Azimuth beamwidth (-6dB) [°]: 2x 140- Antenna gain [dBi]: 22.5 Ports and interfaces- SFP cage: Yes- LAN speed: (1) 100M/1G/10Gbps + (1) 10/100/1000Mbps- Optical interfaces: (1) 1/10Gbps Power supply- Power over Ethernet: 802.3bt, 42 ... 57V DC- Power supply type: PoE- Max. Power consumption [W]: 35 Physical properties- Protection class: IP67- Operating temperature [°C]: -40 to 60- Weight [g]: 4000- Width [mm]: 185- Height [mm]: 280- Depth [mm]: 102 Software- Management: Web management, Cambium cnMaestro Cloud

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

