

Item no.: US-8-60W-5_EU

US-8-60W-5 - Fully Managed Gigabit Switch, 5-pack

from **546,09 EUR**

Item no.: US-8-60W-5_EU
shipping weight: 4.55 kg
Manufacturer: Ubiquiti



Product Description

US-8-60W-5 - Fully Managed Gigabit Switch, 5-pack
- PLEASE NOTE: THIS IS A 5-PACK -

- Non-blocking throughput switching performance
- Gigabit Ethernet RJ45 ports
- Robust performance for enterprise networks

Overview

Build and expand your network with UniFi Switch, part of the UniFi line of products. The new 8-port models feature Gigabit Ethernet ports in a compact form factor. The switches are fully manageable, delivering robust performance and intelligent switching for your networks. [Switching Performance](#)

The UniFi Switch offers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss. For its total, nonblocking throughput, each UniFi Switch supports up to 8 Gbps with a switching capacity of 16 Gbps. [PoE](#)

The US-8 can be powered by 802.3af/at, 48V passive PoE, or the included power adapter. When the US-8 is powered by 802.3at PoE or the included power supply, port 8 supports 48V (2pair) PoE passthrough to deliver up to 12W of power.

The US-8-60W is powered by its included power adapter. It has four autosensing PoE ports delivering up to 15.4W of power per port. - PLEASE NOTE: THIS IS A 5-PACK -

Model: US-8-60W

- (8) Gigabit RJ45 ports
- (4) auto-sensing IEEE 802.3af PoE ports
- Non-blocking throughput: 8 Gbps
- Switching capacity: 16 Gbps
- Forwarding rate: 11.9 Mpps
- Maximum power consumption: 12 W
- Available in single-pack and 5-pack

Specifications

- Dimensions: 148.0 x 99.5 x 30.7 mm (5.83 x 3.92 x 1.21")
- Weight: 432 g (15.24 oz)
- Enclosure Characteristics: SGCC steel
- Total non-blocking throughput: 8 Gbps
- Switching capacity: 16 Gbps
- Forwarding rate: 11.9 Mpps
- Max. power consumption: 12 W (excluding PoE output)
- Max. PoE wattage per port: 15.4 W
- Power method: 48 V DC, max. 2 A
- Supported voltage range: 57 V DC to 44 V DC
- Power supply: External AC/DC adapter, 48 V, 1.25 A
- LEDs: PoE (port 8), speed/link/activity (all ports)
- Networking interfaces: (8) 10/100/1000 Mbps RJ45 ports
- PoE interfaces (4) ports 5, 6, 7, 8; IEEE 802.3af
- ESD/EMP protection:
 - Air: +/- 24 kV
 - Contact: +/- 24 kV
- Operating temperature: -5°C to 45° C (23°F to 113°F)
- Operating humidity: 5 to 95% non-condensing
- Shock and vibration: ETSI300-019-1.4 Standard
- Certifications: CE, FCC, IC

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

