

Item no.: AFI-ALN

AFI-ALN-EU - AFI-ALN - AmpliFi Alien Router and MeshPoint

from **779,88 EUR**

shipping weight: 0.10 kg Manufacturer: Ubiquiti



Product Description

AFI-ALN - AmpliFi Alien Router and MeshPoint

With the latest 802.11ax Wi-Fi 6 technology, AmpliFi Alien delivers 4x the overall network capacity and 2x the coverage while reaching true Gigabit speeds. It features a dual-band radio with 2.4 GHz and 5 GHz 802.11ax radios optimized for Wi-Fi 6 performance and backwards compatibility with previous Wi-Fi standards. This combination pack comprises one AmpliFi Alien Router and one Amplifi Alien MeshPoint. The MeshPoint expands wireless range coverage and includes a Gigabit Ethernet port to extend wired connectivity

- Dimensions: Router/MeshPoint: 110 x 110 x 250 mm (4.33 x 4.33 x 9.84")
 Weight: Router: 1.2 kg (2.65 lb.); MeshPoint: 1.09 kg (2.4 lb.)
 Supported frequency range: 5.15 5.85 GHz
 Enclosure material: Polycarbonate

Hardware

- Processor: Router/MeshPoint: Quad-Core(R) Cortex(R) A53 at 2 GHz

- Processor: Rotter/MeshPoint: Quad-Core(R) Abs at 2 Gr2
 Memory information: Router/MeshPoint: 1 GB
 Management interface: AmpilFi Wi-Fi App
 Networking interface: Router: (1) 10/100/1000 Mbps RJ45 Ethernet WAN; (4) 10/100/1000 Mbps RJ45 Ethernet LAN; MeshPoint: (1) 10/100/1000 Mbps RJ45 Ethernet LAN
 Max. power consumption: Router: 35 W; MeshPoint: 34 W
 ESD/EMP protection: Router://MeshPoint: Air/contact: +/-24 kV

- Power method: Router/MeshPoint: Universal AC input: 100-240 V AC, 1 A max., 50/60 Hz
- Button: Router/MeshPoint: Factory reset
 Display: Router: 4.7" diagonal, 274 x 1268, 279 ppi, G+F touch, full color; MeshPoint: No display
- Antenna: Router/MeshPoint: Internal dual-band metal stamp with 12 polarity
 Antenna gain: 2.4 GHz: 3 dBi; 5 GHz: 6 dBi
 Max. TX power: 2.4 GHz: 20 dBm; 5 GHz: 36 dBm
 MIMO: 2.4 GHz: 4 x 4; 5 GHz: 8 x 8
 Speeds: 2.4 GHz: 1148 Mbps; 5 GHz: 4800 Mbps

- LED: Router/MeshPoint: Green ring; MeshPoint: Green status indicator; Flashing: Initial configuration; Lights up in sequence bottom to top: Bootup in progress; Lights up in sequence from the middle outwards: Wi-Fi not ready or connected; Steady: Device is adopted (lit based on the signal strength receiving from the router); Flash quickly: Locate; Lights up one by one: Firmware upgrading

 Operating temperature: Router/MeshPoint: -10°C to 45°C (14°F to 113°F)

 Operating humidity: Router/MeshPoint: 5 to 95% non-condensing

 Certifications: Router/MeshPoint: CE, FCC, IC

Software

- Wi-Fi standards: Up to Wi-Fi 6
 Wi-Fi functions: MU-MIMO, OFDMA, Tx-beamforming
 Power save: Yes
 Wireless security: WPA2
 VLAN: Yes
 Advanced QoS: Yes
 Guest traffic isolation: Yes
 Concurrent clients: Yes
 Supported data rates: 802.11a: 54 Mbps; 802.11b: 11 Mbps; 802.11g: 54 Mbps; 802.11n: 600 Mbps + 600 Mbps; 802.11ac: 1733 Mbps + 800 Mbps; 802.11ax: (backbone) 4800 Mbps router-mesh connection, 802.11ax: (available to clients) 4800 Mbps + 1148 Mbps
 Operating frequency*: 2.4 GHz: 2412 2472 MHz; 5 GHz: 5150 5875 MHz

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability



^{*}Depends on regulatory region.