

Item no.: 387415

45MR-6810-T - Module for the ioThinX 4500 series, 8 TCs

from **400,40 EUR**

Item no.: 387415
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa's advanced controllers and I/O products facilitate the realisation of complex IIoT applications such as energy management, factory machine management, transportation management and remote asset management through expandable communication and high-performance data acquisition and control capabilities. Use the ioThinX 4500 Series Power Calculator to calculate how many power modules are required for your application.

45MR-6810-T ioThinX 4500 Series (45MR) Modules

Module for the ioThinX 4500 Series, 8 TCs, -40 to 75°C operating temperature

Input/output interface- Thermocouple channels: 8- Insulation: 3k VDC or 2k Vrms

ThermocouplesConnection: Spring Euroblock terminal

Sensor type: J, K, T, E, R, S, B, N

millivolt type- ± 19.532 mV- ± 39.062 mV- ± 78.126 mV

Resolution: 16 bits

millivolt accuracy:- $\pm 0.1\%$ FSR @ 25°C- $\pm 0.3\%$ FSR @ -40 and 75°C

Sampling rate:- All channels: 12 samples/sec.- Per channel: 5 samples/sec. Per channel: 1.5 samples/sec

Input impedance: 1 mega-ohm (min.)

Power consumption- System power: 148.1 mA @ 3.3 VDC

Physical characteristics- Housing: Plastic- Dimensions: 19.5 x 99 x 60.5 mm (0.77 x 3.90 x 2.38 in)- Weight: 78.4 g (0.173 lb)- Installation: DIN rail mounting- Stripping length: I/O cable, 9 to 10 mm- Wiring: 18 to 24 AWG

Environmental conditions- Operating temperature: -40 to 75°C (-40 to 167°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Relative humidity: 5 to 95% (non-condensing)- Altitude: Up to 4000 metres

Standards and certificationsEMC: EN 55032/35EMI: CISPR 32, FCC Part 15B Class AEMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 3 V- IEC 61000-4-8 PFMFShock: IEC 60068-2-27Vibration: IEC 60068-2-6Safety: UL 61010-2-201

Hazardous areas: ATEX, Class I Division 2DeclarationEnvironmentally friendly product: RoHS, CRoHS, WEEE

MTBF- Time: 1,649,892 hours- Standards: Telcordia SR332

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

