

Item no.: 387808

EDS-208A-MM-SC-T - Unmanaged Ethernet switch with 6 10100BaseT(X) ports

from **412,27 EUR**

Item no.: 387808
shipping weight: 0.30 kg
Manufacturer: MOXA



Product Description

Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multimode ports with SC connectors, -40 to 75 °C operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector):- 6- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection 100BaseFX ports (multi-mode SC connection):- 2 Standards:- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control Switch features- MAC Table Size: 2 K- Packet Buffer Size: 768 kbits- Processing Type: Store and Forward Performance parameters- Connection: 1 detachable 4-contact terminal block(s)- Input current: 0.15 A @ 24 VDC- Input voltage: 12/24/48 VDC, redundant dual inputs- Operating voltage: 9.6 to 60 VDC- Overload current protection: Supports- Reverse polarity protection: Supports DIP switch configuration- Ethernet interface: Broadcast storm protection Physical properties- Housing: Aluminium- I P protection class: IP30- Dimensions: 50 x 114 x 70 mm (1.96 x 4.49 x 2.76 in)- Weight: 275 g (0.61 lb)- Installation: DIN rail mounting, wall mounting (with optional kit) Environmental conditions- Operating temperature: -40 to 75°C (-40 to 167°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Relative humidity: 5 to 95% (non-condensing) Standards and certifications- Safety: UL 508, EN 62368-1 (LVD)- EMC: EN 55032/35- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Hazardous areas: ATEX, Class I Division 2- Railway: EN 50121-4- Traffic control: NEMA TS2- Vibration: IEC 60068-2-6- Shock: IEC 60068-2-27- Free fall: IEC 60068-2-31- Maritime: ABS, LR, NK, DNVMTBF- Time: EDS-208A: 3.248,014 hours EDS-208A-MM/SS: 2,705,157 hours EDS-208A-M/S: 2,943,335 hours- Standards: Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

