

Item no.: 387803

EDS-2005-ELP - Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, p

from **83,55 EUR**

Item no.: 387803
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Unmanaged Switches Moxa has a large portfolio of industrial unmanaged switches that have been specifically designed for industrial Ethernet infrastructure. Our unmanaged Ethernet switches uphold the stringent standards that are required for operational reliability in harsh environments. EDS-2005-ELP EDS-2005-ELP Series Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature Ethernet Interface 10/100BaseT(X) Ports (RJ45 connector): 5 Full/Half duplex mode Auto MDI/MDI-X connection Auto negotiation speed Standards: IEEE 802.3 for 10BaseT IEEE 802.1p for Class of Service IEEE 802.3u for 100BaseT(X) IEEE 802.3x for flow control Switch Properties Processing Type: Store and Forward MAC Table Size: 2K Packet Buffer Size: 768 kbits DIP Switch Configuration Ethernet Interface: Quality of Service (QoS), Broadcast Storm Protection (BSP) Power Parameters Connection: 1 removable 3-contact terminal block(s) Input Current: 0.039 A @ 24 VDC Input Voltage: 12/24/48 VDC Operating Voltage: 9.6 to 60 VDC Overload Current Protection: Supported Reverse Polarity Protection: Supported Physical Characteristics Dimensions: 19 x 81 x 65 mm (0.74 x 3.19 x 2.56 in) Installation: DIN-rail mounting Wall mounting (with optional kit) Weight: 74 g (0.16 lb) Housing: Plastic Environmental Limits Ambient Relative Humidity: 5 to 95% (non-condensing) Operating Temperature: -10 to 60°C (14 to 140°F) Storage Temperature (package included): -40 to 85°C (-40 to 185°F) Standards and Certifications Safety: UL 61010-2-201 EN 62368-1 EMC: EN 55032/35 EN 61000-6-2/-6-4 EMI: CISPR 22, 32, FCC Part 15B Class A EMS: IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFM Shock: IEC 60068-2-27 Vibration: IEC 60068-2-6 Freefall: IEC 60068-2-32

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

